

## Eaton 030851

Eaton Moeller® series PKZ0 Rotary handle,  
lockable AK-PKZ0

<b>PRODUCT NAME</b>	Eaton Moeller® series PKZ0 Accessory Lockable Rotary Handle
<b>CATALOG NUMBER</b>	030851
<b>PRODUCT LENGTH/DEPTH</b>	26 mm
<b>PRODUCT HEIGHT</b>	32 mm
<b>PRODUCT WIDTH</b>	26 mm
<b>PRODUCT WEIGHT</b>	0.01 kg
<b>CERTIFICATIONS</b>	CSA File No.: 165628 IEC/EN 60947-4-1 UL 508 UL CSA-C22.2 No. 14 CE UL Category Control No.: NLRV CSA CSA Class No.: 3211-05 UL File No.: E36332
<b>CATALOG NOTES</b>	Cannot be used in combination with VHI20- PKZ0.

<b>USED WITH</b>	P-SOL and PKZ-SOL
<b>PRODUCT CATEGORY</b>	Accessories
<b>FEATURES</b>	Lockable
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND</b>	Meets the product

<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00004316.pdf</a>
	<a href="#">DA-DC-00004601.pdf</a>
	<a href="#">DA-DC-00004246.pdf</a>
	<a href="#">DA-DC-00004545.pdf</a>
	<a href="#">DA-DC-00004244.pdf</a>
	<a href="#">eaton-manual-motor-starters-pkz0-rotary-handle-dimensions.eps</a>
	<a href="#">eaton-manual-motor-starters-circuit-breaker-pkzm4-dimensions.eps</a>
	<a href="#">eaton-manual-motor-starters-rotary-handle-pkz0-rotary-handle-3d-drawing.eps</a>

<b>CREEPAGE DISTANCES</b>	standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>COLOR</b>	Black
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	55 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>THICKNESS</b>	6.35 mm
<b>DEGREE OF PROTECTION</b>	NEMA Other
<b>SUITABLE FOR</b>	Switch disconnectors
<b>LOCKING FACILITY</b>	Lockable in the 0 (Off) position (with padlock)
<b>FUNCTIONS</b>	For locking motor-protective circuit-breakers PKZM0, PKZM4 and PKE as

---

a main switch in  
compliance with EN 60204

---

---

**PROJECT NAME:**

---

**PROJECT NUMBER:**

---

**PREPARED BY:**

---

:

---



Eaton House  
30 Pembroke Road  
Dublin 4,  
Eaton.com

© 2025

Follow us on social media to get the  
latest product and support  
information.

