

## Eaton 106778

Eaton Moeller® series LS Position switch, 2 N/C, basic, spring force

<b>PRODUCT NAME</b>	Eaton Moeller® series LS Position switch
<b>CATALOG NUMBER</b>	106778
<b>PRODUCT LENGTH/DEPTH</b>	55 mm
<b>PRODUCT HEIGHT</b>	170 mm
<b>PRODUCT WIDTH</b>	37 mm
<b>PRODUCT WEIGHT</b>	0.417 kg
<b>CERTIFICATIONS</b>	UL Category Control No.: NKCR CSA Class No.: 3211-03 CSA-C22.2 No. 14 CSA File No.: 012528 IEC/EN 60947-5 CSA UL 508 UL CE IEC/EN 60947 UL File No.: E29184

<b>TYPE</b>	<ul style="list-style-type: none"> <li>• Position switch</li> <li>• Safety position switch</li> </ul>
<b>FEATURES</b>	Expandable Forced opening
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to

<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">DA-DC-00004361.pdf</a>
	<a href="#">DA-DC-00004360.pdf</a>
	<a href="#">eaton-position-switches-contact-ls-wiring-diagram-006.eps</a>

	be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>ELECTRIC CONNECTION TYPE</b>	Cable entry metrical
<b>ENCLOSURE MATERIAL FINISHING</b>	Other
<b>FITTED WITH:</b>	Auxiliary release mechanism Interlock monitoring
<b>OPERATING FREQUENCY</b>	800 Operations/h
<b>POLLUTION DEGREE</b>	3
<b>ACTUATOR ALIGNMENT</b>	Other
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>ENCLOSURE MATERIAL</b>	Plastic Insulated material
<b>ENCLOSURE TYPE</b>	Cuboid
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V</b>	0.8 A
<b>RATED OPERATIONAL</b>	0.8 A

<b>CURRENT (IE) AT DC-13, 125 V</b>	
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V</b>	0.3 A
<b>RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V</b>	3 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	6 A
<b>SENSOR HEIGHT</b>	173 mm
<b>SENSOR LENGTH</b>	39 mm
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>WIDTH SENSOR</b>	60 mm
<b>PRODUCT CATEGORY</b>	Basic units with spring-powered interlock (closed-circuit principle)
<b>ACTION</b>	2020122120328-Mechanical Limit Switches.xlsm-Data
<b>FORCE FOR POSITIVE OPENING - MIN</b>	50 N
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	4000 V AC
<b>ACTUATING FORCE AT BEGINNING/END OF STROKE</b>	25 N/15 N (plug-in/pull-out)
<b>EXPLOSION SAFETY CATEGORY FOR DUST</b>	None
<b>EXPLOSION SAFETY CATEGORY FOR GAS</b>	None
<b>ACTUATOR TYPE</b>	None
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>DIAMETER SENSOR</b>	0 mm
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER</b>	0.13 W

<b>POLE, CURRENT-DEPENDENT PVID</b>	
<b>NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)</b>	0
<b>NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)</b>	2
<b>NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)</b>	0
<b>NUMBER OF SAFETY AUXILIARY CONTACTS</b>	2
<b>RATED INSULATION VOLTAGE (UI)</b>	400 V
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 125 V</b>	6 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V</b>	6 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 24 V</b>	6 A
<b>RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V</b>	4 A
<b>MOUNTING POSITION</b>	As required
<b>RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ)</b>	1 kA
<b>OVERVOLTAGE CATEGORY</b>	III
<b>CONNECTION TYPE</b>	Screw terminal
<b>DUTY FACTOR</b>	100 % (Magnet)
<b>DEGREE OF PROTECTION</b>	IP65 NEMA Other
<b>INTERFACE TYPE</b>	None
<b>SWITCH FUNCTION TYPE</b>	Slow-action switch
<b>VOLTAGE TOLERANCE</b>	1.1 x Us, Pick-up and drop-out values 0.85 x Us, Pick-up and drop-out values
<b>SCREW SIZE</b>	PH1, Terminal screw
<b>LIFESPAN</b>	1,000,000 mechanical Operations
<b>RATED CONTROL SUPPLY VOLTAGE</b>	120 V 50/60 Hz (Us, for magnet drive)

<b>REPETITION ACCURACY</b>	0.02 mm (Contacts/switching capacity)
<b>SHOCK RESISTANCE</b>	10 g, Standard-action contact, Mechanical, Half-Sinusoidal shock 20 ms
<b>MECHANICAL HOLDING FORCE</b>	1600 N (according to GS-ET-19 (04/2004), XWA, XFG, XF) 1700 N (according to GS-ET-19 (04/2004), XG, XW, XNG) 1200 N (according to GS-ET-19 (04/2004), XNW)
<b>SUPPLY FREQUENCY</b>	Max. 400 Hz, Contacts
<b>SUITABLE FOR</b>	Safety functions
<b>POWER CONSUMPTION</b>	8 VA at 120 V AC (electromechanical actuation) 8 W at 24 V DC (electromechanical actuation) 11 VA at 230 V AC (electromechanical actuation)
<b>TIGHTENING TORQUE</b>	0.9 Nm, Screw terminals
<b>SHORT-CIRCUIT PROTECTION RATING</b>	Max. 6 A gG/gL, Fuse, Contacts
<b>TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)</b>	1 x (0.5 - 1.5) mm <sup>2</sup> 2 x (0.5 - 1.5) mm <sup>2</sup>
<b>TERMINAL CAPACITY (SOLID)</b>	1 x (0.75 - 2.5) mm <sup>2</sup> 2 x (0.75 - 1.5) mm <sup>2</sup>

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

:



Eaton House  
30 Pembroke Road  
Dublin 4,  
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

