

Eaton 107198

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Profile terminal 41x20-42

PRODUCT NAME	Eaton xEffect SASY 60i busbar terminal
CATALOG NUMBER	107198
PRODUCT LENGTH/DEPTH	72 mm
PRODUCT HEIGHT	118 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.66 kg
COMPLIANCES	UL CSA09 (refer to approbation report) RoHS conform
CERTIFICATIONS	North America (UL listed, CSA certified) CE marking CSA-C22.2 No. 14 CSA (Class No. 3211-37) UL (Category Control Number NMTR2, NMTR8) UL (File No. E307559) IEC 60439-1 CSA (File No. 236217) UL508A

USED WITH	Feeder circuits
	Double T profile
	Connection
	185 mm system
	60 mm system
SPECIAL FEATURES	- Termination to busbars without drilling - Put a spacer between the laminated copper busbars when connecting in parallel
TYPE	185 mm system 60 mm system - Connection
WIDTH CLAMP	72 mm
DEGREE OF PROTECTION	UL508A; CSA-C22.2 No. 14;
	IEC 60439-1; CE marking
VOLTAGE RATING (UL CSA 13)	Feeder circuits
BUSBAR THICKNESS - MAX	Max. 600 V AC
BUSBAR THICKNESS - MIN	40 mm
BUSBAR WIDTH - MAX	40 mm
BUSBAR WIDTH - MIN	30 mm
CONDUCTOR CROSS SECTION - MAX	30 mm
RATED OPERATIONAL CURRENT (IE) - MAX	800 mm ²
FUNCTIONS	1600 A
	Current limiting circuit breaker, refer to approbation report
	Connections
RATED OPERATION CURRENT (IE)	Profile terminal
SUITABLE FOR	1600 A
	Strip conductor connection
	T-rail
RATED OPERATIONAL CURRENT	
	1600 A

eaton-akp-750-800-900-1000-1200-1600-2000-3600-il123005zu.pdf
eaton-control-panels-xeffect-sasy-profile-terminal-3d-drawing.eps

TERMINAL CAPACITY	800 mm ² (Cu band)
(CONDUCTOR)	20 mm - 42 mm (41x)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

