# Eaton 114726

Eaton xEnergy Light LV systems LV switchgear. Side walls (1 pair), closed, for HxD = 1800 x 500mm, IP55, grey

| 口口口口 | |
|---|---|
| **PRODUCT NAME** | Eaton xEnergy Light LV systems LV switchgear |
| **CATALOG NUMBER** | 114726 |
| **PRODUCT LENGTH/DEPTH** | 1800 mm |
| **PRODUCT HEIGHT** | 50 mm |
| **PRODUCT WIDTH** | 390 mm |
| **PRODUCT WEIGHT** | 19.4 kg |
| **COMPLIANCES** | RoHS conform |

| | |
|---|---|
| **USED WITH** | Accessory<br>Control centres XVTL<br>Combination enclosure |
| **SPECIAL FEATURES** | Countersunk screws included as standard\nEnclosure side plates, in pairs\nExternal fixing with self-threading, self-grounding countersunk screws |
| **TYPE** | Accessory\nCombination enclosure\nControl centres XVTL |
| **ACCESSORY/SPARE PART TYPE** | Enclosure side plates |
| **SURFACE FINISHING** | Polyester powder coating<br>Powder coating<br>RAL 7035, light gray |
| **COLOR** | Gray |
| **DEGREE OF PROTECTION** | IP55 |
| **UNIT TYPE** | Modular system |
| **MODULAR SPACING** | 25 mm |
| **NUMBER OF HEIGHT UNITS** | 0 |
| **RAL-NUMBER** | 7035 |
| **SUITABLE FOR ENCLOSURE BUILDING LENGTH/DEPTH** | 500 mm |
| **SUITABLE FOR HEIGHT** | 1800 mm |
| **SUITABLE FOR LENGTH/DEPTH** | 500 mm |
| **MATERIAL** | Sheet steel 1.25 mm<br>Steel |
| **HOUSING MATERIAL** | Sheet steel 1.25 mm |
| **SUITABLE FOR** | Side panel use |
| **FUNCTIONS** | Combination enclosure<br>Enclosure side plates for protection type IP55 to IEC/EN 60529 and IEC/EN 529<br>For terminating a panel row |

| | |
|---|---|
| 产品目录 | [eaton-xenergy-light-add-on-distribution-board-product-catalog-2017-en-us.pdf](eaton-xenergy-light-add-on-distribution-board-product-catalog-2017-en-us.pdf)<br><br>[eaton-pdd-xenergy-light-catalog-ca014022en-en-us.pdf](eaton-pdd-xenergy-light-catalog-ca014022en-en-us.pdf) |

| | |
|---|---|
| 🔲🔲🔲🔲: | |
| 🔲🔲🔲🔲: | |
| 🔲🔲🔲: | |
| 🔲🔲: | |

🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲🔲