

Eaton 116898

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, +additional handle red, size 2, NA type

PRODUCT NAME	Eaton Moeller series NZM operating element NA
CATALOG NUMBER	116898
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	432 mm
PRODUCT WIDTH	105 mm
PRODUCT WEIGHT	0.806 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	UL489 UL508A NFPA79 UL listed Specially designed for North America CSA (File No. 22086) CE marking UL (Category Control Number DIHS) CSA certified IEC60947 CSA-C22.2 No. 5-09 CSA (Class No. 1437-01) UL (File No. E140305)

USED WITH	PN2(-4) N(S)2(-4) NZM2(-4)
FEATURES	With red door coupling rotary handle for use of switch as emergency switching off device Lockable
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL	Does not apply, since the

eaton-door-coupling-handle-north-america-variant-nzm2-xhb-il01206008z.pdf
eaton-circuit-breaker-switch-nzm-mccb-dimensions.eps
eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-005.eps

IMPACT	entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Red
FITTED WITH:	<p>Add-on rotary handle on switch with "Deliberate Action" operation as per NFPA79 and UL508A Part 2</p> <p>Black and yellow lightning symbol</p> <p>Door coupling rotary handle with rotary drive</p> <p>Extension shaft</p> <p>External warning plate/markings plate in German/English</p> <p>Padlock</p> <p>Extension shaft NZM...-XV6 for mounting depth 600 mm</p>
FRAME	NZM2
SUITABLE FOR	<p>Power circuit breaker</p> <p>Emergency stop</p> <p>Switch disconnectors</p>

COVER/DOOR TYPE	<p>With activated door interlock. Cannot be opened in ON, OFF, or TRIP. Can only be opened in RESET.</p> <p>Door interlock can be modified such that it can be defeated from the outside using a screwdriver</p> <p>Door interlock not defeated in the locked OFF position.</p> <p>Door interlock on OFF with max. 3 padlocks</p>
LOCKING FACILITY	<p>Lockable on the 0 position on the handle using up to 3 padlocks</p> <p>Lockable on the switch in the 0 position</p> <p>Can also be modified in I position</p> <p>With door interlock</p>
TYPE	<ul style="list-style-type: none"> • Accessory • Main switch assembly kit
SPECIAL FEATURES	<ul style="list-style-type: none"> • External warning plate/designation label can be clipped on. • For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. • Kit for use as a main switch
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	<p>IP66</p> <p>4X. 12</p>

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

