Eaton 125LEC

Eaton Bussmann series high speed British standard fuse, 125 A, 240 V, None, aR (accompanied semiconductor protection)

Eaton Bussmann series high speed british standard fuse
125LEC
46 mm
45 mm
115 mm
28.9 g
CE Marked RoHS Compliant
BS88 IEC 60269 UL Recognized



AMPERAGE RATING	125 A
BREAKING CAPACITY	200 kA
FUSE INDICATOR	None
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC/DC
RATED SWITCHING CAPACITY	200 kA
RATED VOLTAGE AC	240 V
RATED VOLTAGE DC	150 V
CURRENT TYPE	AC/DC
CLASS	Class aR
CLASS WATT LOSSES	Class aR 16 W
WATT LOSSES	16 W
WATT LOSSES FUSE SHAPE	16 W Radial bladed tags
WATT LOSSES FUSE SHAPE COLOR	16 W Radial bladed tags None
WATT LOSSES FUSE SHAPE COLOR CONSTRUCTION SIZE	16 W Radial bladed tags None Other
WATT LOSSES FUSE SHAPE COLOR CONSTRUCTION SIZE VOLTAGE RATING	16 W Radial bladed tags None Other 240 V
WATT LOSSES FUSE SHAPE COLOR CONSTRUCTION SIZE VOLTAGE RATING TYPE	16 W Radial bladed tags None Other 240 V Fuse Semiconductor, DC Common bus, DC drives, power

	eaton-high-speed-british-
DECLARATIONS OF	standard-fuse-declaration-
CONFORMITY	of-conformity-
	<u>uk250923en.pdf</u>

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
:	



Eaton House 30 Pembroke Road Dublin 4, Eaton.com Follow us on social media to get the latest product and support information.









