



□□□□

Eaton 144905

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, handle black, +additional handle, shaft 600mm

□□□□

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	144905
PRODUCT LENGTH/DEPTH	580 mm
PRODUCT HEIGHT	100 mm
PRODUCT WIDTH	140 mm
PRODUCT WEIGHT	0.795 kg
COMPLIANCES	UL/CSA IEC RoHS conform



Powering Business Worldwide

USED WITH	NZM1(-4) PN1(-4) N(S)1(-4)
FEATURES	Lockable With black door coupling rotary handle
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FITTED WITH:	<p>Add-on rotary handle on switch with "Deliberate Action" operation as per NFPA79 and UL508A Part 2</p> <p>Door coupling rotary handle with rotary drive</p> <p>Extension shaft NZM...-XV6 for mounting depth 600 mm</p> <p>External warning plate/marketing plate in German/English</p> <p>Black and yellow lightning symbol</p> <p>Extension shaft</p> <p>Padlock</p>
FRAME	NZM1
SUITABLE FOR	Power circuit breaker Switch disconnecter
COVER/DOOR TYPE	<p>Door interlock on OFF with max. 3 padlocks</p> <p>Door interlock not defeated in the locked OFF position.</p> <p>Door interlock can be modified such that it can be defeated from the outside using a</p>

