



Eaton 167622

Eaton Moeller series xPole - SPCT2 Surge Protection Device. Plug-in surge arresters, 3pole+N, 335VAC, 20 kA



PRODUCT NAME	Eaton Moeller series xPole - SPCT2 Surge protection device
CATALOG NUMBER	167622
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	67 mm
PRODUCT WIDTH	70 mm
PRODUCT WEIGHT	0.408 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	CE



Powering Business Worldwide

□□□□

FEATURES	Category type 2
FRAME	4 modular spacing
DEGREE OF PROTECTION	IP20
MOUNTING METHOD	DIN rail (top hat rail) 35 mm
SIGNALLING AT THE DEVICE	Optic
SYSTEM CONFIGURATION TYPE	TN-C-S Other TT TN TN-S IT
TYPE	Surge arrester
APPLICATION	<ul style="list-style-type: none"> • Open areas • Residential buildings • Utility buildings
CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MAX	35 mm ²
CONDUCTOR CROSS SECTION (FLEXIBLE, FINE-STRAND) - MIN	35 mm ²
CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MAX	25 mm ²
CONDUCTOR CROSS SECTION (SOLID, SOLID-STRAND) - MIN	25 mm ²
CONTINUOUS VOLTAGE AT AC - MAX	335 V
DISCHARGE SURGE CURRENT (8/20) - MAX	40 kA
NOMINAL DISCHARGE SURGE CURRENT (8/20)	20 kA
NOMINAL VOLTAGE AT AC	335 V
NUMBER OF CONDUCTORS WITHOUT EARTHING	3
VOLTAGE PROTECTION LEVEL	1.6 kV
OVERCURRENT PROTECTION DEVICE, SERIES CONNECTION (FUSE) - MAX	125 A

□□

□□□	eaton-xpole-spct2-surge-protection-device-wiring-diagram.jpg
□□□□	eaton-spct2-surge-protection-catalog-ca010005en-en-us.pdf
□□	eaton-xpole-spct2-surge-protection-device-dimensions-002.jpg

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

□□:



□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□□
Eaton.com

© 2025 □□ □□□□□□□□

Follow us on social media to get the latest product and support information.

