

# Eaton 169401

Eaton DA1 Variable frequency drive, 400 V AC, 3-phase, 150 A, 75 kW, IP55/NEMA 12, Radio interference suppression filter, OLED display, DC link choke

<b>PRODUCT NAME</b>	Eaton DA1 Variable frequency drive
<b>CATALOG NUMBER</b>	169401
<b>PRODUCT LENGTH/DEPTH</b>	313.5 mm
<b>PRODUCT HEIGHT</b>	865 mm
<b>PRODUCT WIDTH</b>	330 mm
<b>PRODUCT WEIGHT</b>	50 kg
<b>CERTIFICATIONS</b>	UL File No.: E172143 EAC IEC/EN61800-3 RoHS, ISO 9001 CE RCM IEC/EN 61800-3 DNV UL CUL UL report applies to both US and Canada IEC/EN61800-5 Specification for general requirements: IEC/EN 61800-2 UL Category Control No.: NMMS, NMMS7 Certified by UL for use in Canada UL 508C Safety: EN 61800-5-1: 2003  UkrSEPRO CSA-C22.2 No. 14
<b>CATALOG NOTES</b>	The brake resistors are assigned based on the maximum rated power of the variable frequency

drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.

<b>PRODUCT CATEGORY</b>	Variable frequency drives
<b>FEATURES</b>	Parameterization: Fieldbus
	Parameterization: Keypad
	Parameterization: drivesConnect
	Parameterization: drivesConnect mobile (App)
<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Meets the product standard's requirements.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.

<b>DECLARATIONS OF CONFORMITY</b>	<a href="#">eaton-variable-frequency-drive-declaration-of-conformity-uk251145en.pdf</a>
<b>INSTALLATION VIDEOS</b>	<a href="#">Video PowerXL DA1</a>
	<a href="#">eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf</a>
	<a href="#">eaton-powerxl-da1-application-manual-mn04020006z-en-us.pdf</a>
	<a href="#">eaton-powerxl-da1-installation-manual-mn04020005z-en-us.pdf</a>
	<a href="#">eaton-frequency-inverter-dimensions-025.eps</a>
	<a href="#">eaton-frequency-inverter-3d-drawing-016.eps</a>

<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FITTED WITH:</b>	DC link choke PC connection Radio interference suppression filter Breaking resistance IGBT inverter Brake chopper Internal DC link OLED display Control unit Additional PCB protection
<b>CLIMATIC PROOFING</b>	< 95 average relative humidity (RH), no condensation, no corrosion
<b>CONNECTION TO SMARTWIRE-DT</b>	In conjunction with DX-NET-SWD1 SmartWire DT module Yes
<b>OPERATING MODE</b>	U/f control Speed control with slip compensation

	Sensorless vector control (SLV) Optional: Vector control with feedback (CLV)
<b>FRAME SIZE</b>	FS6
<b>ALTITUDE</b>	Max. 1000 m Above 1000 m with 1 % derating per 100 m Max. 4000 m
<b>ENVIRONMENTAL CLASS</b>	3C2, 3S2 (Air quality)
<b>APPLICATION IN DOMESTIC AND COMMERCIAL AREA PERMITTED</b>	Yes
<b>MAINS SWITCH-ON FREQUENCY</b>	Maximum of one time every 30 seconds
<b>APPLICATION IN INDUSTRIAL AREA PERMITTED</b>	Yes
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-10 °C
<b>AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MAX</b>	40 °C
<b>AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MIN</b>	-10 °C
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-40 °C
<b>APPARENT POWER AT 400 V</b>	103.92 kVA
<b>APPARENT POWER AT 480 V</b>	124.71 kVA
<b>ASSIGNED MOTOR CURRENT IM AT 400 V, 50 HZ, 150% OVERLOAD</b>	134 A
<b>MOUNTING POSITION</b>	Vertical
<b>RELATIVE SYMMETRIC NET FREQUENCY TOLERANCE</b>	10 %
<b>RELATIVE SYMMETRIC NET VOLTAGE TOLERANCE</b>	10 %
<b>PROTECTION</b>	Finger and back-of-hand proof, Protection against

	direct contact (BGV A3, VBG4)
<b>RESOLUTION</b>	0.1 Hz (Frequency resolution, setpoint value)
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>SWITCH-ON THRESHOLD FOR THE BRAKING TRANSISTOR</b>	780 VDC
<b>VOLTAGE RATING - MAX</b>	480 VAC
<b>COMMUNICATION INTERFACE</b>	CANopen®, built in DeviceNet, optional Modbus RTU, built in OP-Bus (RS485), built in PROFIBUS, optional Modbus-TCP, optional Ethernet IP, optional EtherCAT, optional SmartWire-DT, optional PROFINET, optional
<b>CONVERTER TYPE</b>	U converter
<b>DEGREE OF PROTECTION</b>	NEMA 12 IP55
<b>PROTOCOL</b>	CAN PROFINET IO DeviceNet PROFIBUS MODBUS Other bus systems EtherNet/IP TCP/IP
<b>ASSIGNED MOTOR CURRENT IM AT 440 - 480 V, 60 HZ, 150% OVERLOAD</b>	124 A
<b>SYSTEM CONFIGURATION TYPE</b>	AC supply systems with earthed center point
<b>ELECTROMAGNETIC COMPATIBILITY</b>	1st and 2nd environments (according to EN 61800-3)
<b>ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE</b>	100 HP
<b>BRAKING RESISTANCE</b>	6 $\Omega$
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	1575 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W

<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>INPUT CURRENT ILN AT 150% OVERLOAD</b>	164.7 A
<b>BRAKING TORQUE</b>	<p>Max. 30 % MN, Standard - Main circuit</p> <p>Max. 100 % of rated operational current I<sub>e</sub> with external braking resistor - Main circuit</p> <p>Max. 100 % of rated operational current I<sub>e</sub>, variable, DC - Main circuit</p>
<b>CABLE LENGTH</b>	<p>100 m, screened, maximum permissible, Motor feeder</p> <p>300 m, unscreened, with motor choke, maximum permissible, Motor feeder</p> <p>C3 ≤ 25 m, Radio interference level, maximum motor cable length</p> <p>150 m, unscreened, maximum permissible, Motor feeder</p> <p>C2 ≤ 5 m, Radio interference level, maximum motor cable length</p> <p>200 m, screened, with motor choke, maximum permissible, Motor feeder</p>
<b>FUNCTIONS</b>	4-quadrant operation possible
<b>OUTPUT VOLTAGE (U2)</b>	<p>400 V AC, 3-phase</p> <p>480 V AC, 3-phase</p>
<b>NUMBER OF INPUTS (ANALOG)</b>	2
<b>NUMBER OF INPUTS (DIGITAL)</b>	5
<b>RADIO INTERFERENCE CLASS</b>	<p>Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments</p> <p>C2, C3: depending on the motor cable length, the connected load, and ambient conditions.</p> <p>External radio interference</p>

	suppression filters (optional) may be necessary.
<b>NUMBER OF OUTPUTS (DIGITAL)</b>	2
<b>STARTING CURRENT - MAX</b>	200 %, IH, max. starting current (High Overload), for 4 seconds every 40 seconds, Power section
<b>NUMBER OF PHASES (INPUT)</b>	3
<b>NUMBER OF RELAY OUTPUTS</b>	2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
<b>NUMBER OF PHASES (OUTPUT)</b>	3
<b>POWER CONSUMPTION</b>	1575 W
<b>RATED CONTROL SUPPLY VOLTAGE</b>	10 V DC (Us, max. 10 mA)
<b>EFFICIENCY</b>	97.9 % ( $\eta$ )
<b>RATED CONTROL VOLTAGE (UC)</b>	24 V DC (external, max. 100 mA)
<b>SUPPLY FREQUENCY</b>	50/60 Hz
<b>LEAKAGE CURRENT AT GROUND IPE - MAX</b>	2.68 mA
<b>MAINS VOLTAGE - MAX</b>	480 V
<b>MAINS VOLTAGE - MIN</b>	380 V
<b>NOMINAL OUTPUT CURRENT I2N</b>	150 A
<b>NUMBER OF HW-INTERFACES (INDUSTRIAL ETHERNET)</b>	0
<b>NUMBER OF HW-INTERFACES (OTHER)</b>	0
<b>NUMBER OF HW-INTERFACES (PARALLEL)</b>	0
<b>NUMBER OF HW-INTERFACES (RS-232)</b>	0
<b>NUMBER OF HW-INTERFACES (RS-422)</b>	0
<b>NUMBER OF HW-INTERFACES (RS-485)</b>	1
<b>NUMBER OF HW-INTERFACES (SERIAL TTY)</b>	0
<b>NUMBER OF HW-INTERFACES (USB)</b>	0



<b>NUMBER OF INTERFACES (PROFINET)</b>	0
<b>NUMBER OF OUTPUTS (ANALOG)</b>	2
<b>OUTPUT AT LINEAR LOAD AT RATED OUTPUT VOLTAGE - MAX</b>	75 kW
<b>OUTPUT AT QUADRATIC LOAD AT RATED OUTPUT VOLTAGE - MAX</b>	75 kW
<b>OUTPUT FREQUENCY - MAX</b>	500 Hz
<b>OUTPUT FREQUENCY - MIN</b>	0 Hz
<b>OUTPUT VOLTAGE - MAX</b>	500 V
<b>OVERLOAD CURRENT IL AT 150% OVERLOAD</b>	225 A
<b>SUITABLE FOR</b>	Branch circuits, (UL/CSA)
<b>SWITCHING FREQUENCY</b>	4 kHz, 4 - 12 kHz adjustable (audible), fPWM, Power section, Main circuit
<b>RATED OPERATIONAL VOLTAGE</b>	480 V AC, 3-phase 400 V AC, 3-phase
<b>SHORT-CIRCUIT PROTECTION RATING</b>	200 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
<b>RATED FREQUENCY - MAX</b>	62 Hz
<b>RATED FREQUENCY - MIN</b>	48 Hz
<b>RATED OPERATIONAL CURRENT (IE) AT 150% OVERLOAD</b>	150 A
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	150 A
<b>RATED OPERATIONAL POWER AT 380/400 V, 50 HZ, 3-PHASE</b>	75 kW
<b>SAFETY FUNCTION/LEVEL</b>	STO (Safe Torque Off, SIL2, PLc Cat 2)
<b>HEAT DISSIPATION AT CURRENT/SPEED</b>	1200 W at 100% current and 0% speed 1530 W at 100% current and 50% speed 1650 W at 100% current and 90% speed 570 W at 25% current and

---

0% speed  
570 W at 25% current and  
50% speed  
700 W at 50% current and  
0% speed  
840 W at 50% current and  
90% speed  
860 W at 50% current and  
50% speed

---

---

**PROJECT NAME:**

---

**PROJECT NUMBER:**

---

**PREPARED BY:**

---

:

---



Eaton House  
30 Pembroke Road  
Dublin 4,  
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

