



□□□□□

Eaton 170E3587

Eaton Bussmann series high speed traction fuse, 160 A, 750 V, gR (general purpose semiconductor protection), compact size 1, slotted center bolted tags

□□□□

PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170E3587
UPC	051712209298
PRODUCT LENGTH/DEPTH	129 mm
PRODUCT HEIGHT	61 mm
PRODUCT WIDTH	43 mm
PRODUCT WEIGHT	942 g
COMPLIANCES	RoHS Compliant IEC

□□□□	
AMPERAGE RATING	160 A
BREAKING CAPACITY	100 kA
VOLTAGE TYPE	DC
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
INSULATED METAL GRIPPING LUGS (IMGL)	No
FUSE INDICATOR	Other
FUSE SIZE	1*
CLASS	Class gR
WATT LOSSES	26 W
FUSE SHAPE	Square body, slotted center bolted tags
PRE ARC (I2T)	7700
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	156 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	750 V
COLOR	None
INTERRUPT RATING	100 kAIC
CONSTRUCTION SIZE	Other
PACKAGING TYPE	Standard
VOLTAGE RATING	750 V
TYPE	Fuse
APPLICATION	traction
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

□□:

□□	
DECLARATIONS OF CONFORMITY	eaton-high-speed-square-body-fuse-declaration-of-conformity-uk251153en.pdf



□□□□
Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2025 □□ □□□□□□

Follow us on social media to get the latest product and support information.

