

Eaton 170M4716

Fuse-link, high speed, 630 A, AC 690 V, size 1, $53 \times 69 \times 136$ mm, aR, IEC, UL, 115 mm fixing centres

| 0000 | |
|-------------------------|---|
| PRODUCT NAME | Eaton Bussmann series high speed square body fuse |
| CATALOG NUMBER | 170M4716 |
| UPC | 051712259651 |
| PRODUCT LENGTH/DEPTH | 58 mm |
| PRODUCT HEIGHT | 54 mm |
| PRODUCT WIDTH | 170 mm |
| PRODUCT WEIGHT | 487 g |
| COMPLIANCES | CE Marked RoHS Compliant |
| CERTIFICATIONS | UL Recognized IEC Rated |



| AMPERAGE RATING | 630 A |
|--|---|
| BREAKING CAPACITY | 200 kA |
| FUSE INDICATOR | None |
| INSULATED METAL GRIPPING LUGS (IMGL) | No |
| UTILIZATION CATEGORY | aR (accompanied semiconductor protection) |
| VOLTAGE TYPE | AC |
| FUSE SIZE | 1 |
| RATED VOLTAGE AC | 690 V |
| CENTER-TO-CENTER DISTANCE OF CONNECTIONS | 114 mm |
| CURRENT TYPE | AC |
| MOUNTING DIMENSION | M12 |
| CLASS | Class aR |
| CLEARING (I2T) | 350000 at 660 V |
| WATT LOSSES | 80 W |
| FUSE SHAPE | Square body, center bolted tags |
| PRE ARC (I2T) | 52000 |
| COLOR | None |
| INTERRUPT RATING | 200 kAIC |
| CONNECTION | Blade end x blade end |
| CONSTRUCTION SIZE | 1 |
| PACKAGING TYPE | Standard |
| VOLTAGE RATING | 690 V |
| TYPE | Fuse |
| APPLICATION | Semiconductor, DC Common bus, DC drives, power converters/rectifiers |
| FUSE TYPE | US Style FU/115 without indicator Bolted tag |
| FUSE SYSTEM (ACCORDING TO IEC 60269) | Other |

| DECLARATIONS OF CONFORMITY | eaton-high-speed-square- body-fuse-declaration-of- conformity- uk250911en.pdf |
|-------------------------------|--|

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| ПП: | |



Eaton House 30 Pembroke Road Dublin 4, □□□ Eaton.com

latest product and support information.







Follow us on social media to get the



