

Eaton 170M5145

Eaton Bussmann series high speed square body fuse, 550A, 100 kAIC, Class aR, DIN 43 620, Standard, Clearing at 1000V: 370000 , Clearing at 1250V: 495000, square body with centre-bolted tags (slotted), Top fuse status indicator, 100W

PRODUCT NAME	Eaton Bussmann series high speed square body fuse
CATALOG NUMBER	170M5145
UPC	051712260213
PRODUCT LENGTH/DEPTH	284 mm
PRODUCT HEIGHT	67 mm
PRODUCT WIDTH	175 mm
PRODUCT WEIGHT	634 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	IEC Rated UL Recognized

AMPERAGE RATING	550 A
BREAKING CAPACITY	100 kA
FUSE INDICATOR	Top fuse status indicator
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
FUSE SIZE	2
RATED VOLTAGE AC	1250 V
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	108 mm
CURRENT TYPE	AC
MOUNTING DIMENSION	M10
CLASS	Class aR
CLEARING (I2T)	370000 at 1000 V, 495000 at 1250 V
WATT LOSSES	100 W
FUSE SHAPE	Square body, slotted center bolted tags
PRE ARC (I2T)	62000
COLOR	None
INTERRUPT RATING	100 kAIC
CONSTRUCTION SIZE	2
MOUNTING METHOD	DIN 43 620
PACKAGING TYPE	Standard
VOLTAGE RATING	1250 V (IEC), 1300 V (UL)
TYPE	Fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
FUSE TYPE	DIN 43653 /110 Visual indicator Bolted tag
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other



PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

