

## Eaton 172842

Eaton Moeller® series SVB Handle, black, lockable, for metal shaft, for padlock, for P1

PRODUCT NAME	Eaton Moeller® series SVB Accessory Handle
CATALOG NUMBER	172842
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	65 mm
PRODUCT WIDTH	65 mm
PRODUCT WEIGHT	0.09 kg
COMPLIANCES	CE

**TYPE**

- Assembly kit
- Main switch assembly kit
- With black rotary handle and black locking ring

**FEATURES**

Lockable

**10.10 TEMPERATURE RISE**

Not applicable.

**10.11 SHORT-CIRCUIT RATING**

Not applicable.

**10.12 ELECTROMAGNETIC COMPATIBILITY**

Not applicable.

**10.13 MECHANICAL FUNCTION**

Not applicable.

**10.2.2 CORROSION RESISTANCE**

Meets the product standard's requirements.

**10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES**

Meets the product standard's requirements.

**10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT**

Meets the product standard's requirements.

**10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS**

Meets the product standard's requirements.

**10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION**

Meets the product standard's requirements.

**10.2.5 LIFTING**

Does not apply, since the entire switchgear needs to be evaluated.

**10.2.6 MECHANICAL IMPACT**

Does not apply, since the entire switchgear needs to be evaluated.

**10.2.7 INSCRIPTIONS**

Meets the product standard's requirements.

**10.3 DEGREE OF PROTECTION OF ASSEMBLIES**

Does not apply, since the entire switchgear needs to be evaluated.

**10.4 CLEARANCES AND CREEPAGE DISTANCES**

Meets the product standard's requirements.

**10.5 PROTECTION AGAINST ELECTRIC SHOCK**

Does not apply, since the entire switchgear needs to be evaluated.

<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>FITTED WITH:</b>	Padlocking feature
<b>COLOR</b>	Black
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	50 °C
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>SWITCHING ANGLE</b>	90 °
<b>DEGREE OF PROTECTION</b>	NEMA Other
<b>SUITABLE FOR</b>	Only for main switch Switch disconnecter
<b>LOCKING FACILITY</b>	Lockable with a maximum of 3 padlocks
<b>LOCKING MECHANISM</b>	Lockable in the 0 (Off) position (interlock)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House  
30 Pembroke Road  
Dublin 4,  
Eaton.com  
© 2025

Follow us on social media to get the latest product and support information.

