



Eaton 180796

Eaton Moeller® series M22 LED element,
Flat Rear, blue, front mounting

□□□□

PRODUCT NAME	Eaton Moeller® series M22 Accessory LED
CATALOG NUMBER	180796
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	14 mm
PRODUCT WEIGHT	0.004 kg
CERTIFICATIONS	UL File No.: E29184 CSA-C22.2 No. 14-05 IEC/EN 60947-5 CSA Class No.: 3211-03 UL IEC 60947-5-1 CSA File No.: 012528 UL Category Control No.: NKCR CSA-C22.2 No. 94-91 UL 508 CSA CE
CATALOG NOTES	Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany

□□□□

FITTED WITH:	Light source Diode
POLLUTION DEGREE	3
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 Dry heat to IEC 60068-2-2
CONNECTION TO SMARTWIRE-DT	No
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
RATED INSULATION VOLTAGE (UI)	250 V
RATED OPERATIONAL CURRENT (IE) - MAX	15 mA
RATED OPERATIONAL CURRENT (IE) - MIN	5 mA
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	30 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	12 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	30 V
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	12 V
VOLTAGE TYPE	AC/DC
FASTENING TYPE	Front fastening
MOUNTING POSITION	As required
LIGHT COLOR	Blue
CONNECTION TYPE	Front fixing
LAMP TYPE	LED
OVERVOLTAGE CATEGORY	III
CONNECTION TYPE	Spring clamp connection

□□

DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-uk251344en.pdf
MCAD MODEL	m22_fled.dwg m22_fled.stp
□□□□□	IL04716002Z
□□	eaton-operating-contact-m22-led-element-dimensions.eps eaton-operating-button-symbol-003.eps eaton-operating-m22-led-element-3d-drawing.eps
□□/□□	RMQ small E-Stop emergency-stop button

(AUXILIARY CIRCUIT)	
DEGREE OF PROTECTION	IP20
LAMP HOLDER	None
POWER CONSUMPTION	Max. 0.26 W
LIFESPAN, ELECTRICAL	100,000 h (at 25°C, according to EN60064)
TERMINAL CAPACITY (STRANDED)	1 x (0.2 - 1.5) mm ²
SHOCK RESISTANCE	50 g, Mechanical, according to IEC/EN 60068-2-27, Half- Sinusoidal shock 11 ms
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (0.25 - 1) mm ² Use WAGO Variocrimp 4 crimping tool; please enquire for others
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 1.5) mm ² Can be plugged without tools 1 x (0.2 - 1.5) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	20

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY: