

Eaton 185779

Eaton DC1 Variable frequency drive, 230 V
AC, 3-phase, 46 A, 11 kW, IP20/NEMA 0,
Brake chopper, FS4

PRODUCT NAME	Eaton DC1 Variable frequency drive
CATALOG NUMBER	185779
PRODUCT LENGTH/DEPTH	211 mm
PRODUCT HEIGHT	418.5 mm
PRODUCT WIDTH	173 mm
PRODUCT WEIGHT	8.4 kg
CERTIFICATIONS	CUL UL CSA-C22.2 No. 14 IEC/EN 61800-3 RCM Certified by UL for use in Canada IEC/EN61800-3 IEC/EN61800-5 Safety requirements: IEC/EN 61800-5-1 UkrSEPRO UL 508C UL report applies to both US and Canada RoHS, ISO 9001 UL File No.: E172143 UL Category Control No.: NMMS, NMMS7 EAC CE Specification for general requirements: IEC/EN 61800-2
CATALOG NOTES	<ul style="list-style-type: none">• Environmental class: 3C2, 3S2• Overload cycle for 60 s every 600 s

FEATURES	Parameterization: drivesConnect Parameterization: drivesConnect mobile (App) Parameterization: Fieldbus
	Parameterization: Keypad
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL	Does not apply, since the

DECLARATIONS OF CONFORMITY	DA-DC-00004555.pdf
	DA-DC-00003964.pdf
	DA-DC-00004552.pdf
	DA-DC-00004184.pdf
INSTALLATION VIDEOS	Video PowerXL DA1
	IL040024ZU
	eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf
	eaton-frequency-inverter-dimensions-011.eps
	eaton-frequency-inverter-3d-drawing-019.eps
	How does the internal motor protection work?
	The OP System Bus - Parameterizing - Control
	DX-COM-STICK3_Connection

IMPACT	entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	7-digital display assembly IGBT inverter Breaking resistance Internal DC link Control unit Brake chopper PC connection Additional PCB protection
CLIMATIC PROOFING	< 95 average relative humidity (RH), no condensation, no corrosion
CONNECTION TO SMARTWIRE-DT	Yes In conjunction with DX-NET-SWD3 SmartWire DT module
OPERATING MODE	U/f control Sensorless vector control (SLV) Speed control with slip compensation BLDC motors PM motors

	Synchronous reluctance motors
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	2000 V
FRAME SIZE	FS4
ALTITUDE	Above 1000 m with 1 % derating per 100 m Max. 4000 m
APPLICATION IN DOMESTIC AND COMMERCIAL AREA PERMITTED	Yes
MAINS SWITCH-ON FREQUENCY	Maximum of one time every 30 seconds
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE - MIN	-10 °C
MAINS VOLTAGE - MAX	240 V
OUTPUT VOLTAGE - MAX	250 V
RATED OPERATIONAL POWER AT 220/230 V, 50 HZ, 3-PHASE	11 kW
RELATIVE SYMMETRIC NET FREQUENCY TOLERANCE	10 %
RELATIVE SYMMETRIC NET VOLTAGE TOLERANCE	10 %
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MAX	50 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MIN	-10 °C
AMBIENT STORAGE TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
APPARENT POWER AT 230 V	10.58 kVA
APPARENT POWER AT 240 V	11.04 kVA
APPLICATION IN INDUSTRIAL AREA PERMITTED	Yes
HEAT DISSIPATION	Operation (with 150 %

DETAILS	overload)
PRODUCT CATEGORY	Variable frequency drives
PROTECTION	Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
RESOLUTION	0.1 Hz (Frequency resolution, setpoint value)
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
SWITCH-ON THRESHOLD FOR THE BRAKING TRANSISTOR	390 VDC
VOLTAGE RATING - MAX	240 V
MOUNTING POSITION	Vertical
OVERVOLTAGE CATEGORY	III
COMMUNICATION INTERFACE	CANopen®, built in OP-Bus (RS485), built in Modbus RTU, built in SmartWire-DT, optional
CONVERTER TYPE	U converter
DEGREE OF PROTECTION	IP20 NEMA Other
ASSIGNED MOTOR POWER AT 220/230 V, 60 HZ, 3-PHASE	15 HP
BRAKING RESISTANCE	10 Ω
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	446 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
INPUT CURRENT ILN AT 150% OVERLOAD	50.1 A
MAINS CURRENT DISTORTION	120 %
ASSIGNED MOTOR CURRENT IM AT 220 - 240 V, 60 HZ, 150% OVERLOAD	46 A
ASSIGNED MOTOR CURRENT IM AT 230 V, 50	46 A

HZ, 150% OVERLOAD	
PROTOCOL	MODBUS Other bus systems EtherNet/IP CAN
OVERLOAD CURRENT I_L AT 150% OVERLOAD	69 A
RATED FREQUENCY - MAX	62 Hz
RATED FREQUENCY - MIN	48 Hz
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	46 A
SYSTEM CONFIGURATION TYPE	AC supply systems with earthed center point
BRAKING CURRENT	≤ 0.6 A (max. 6 A for 120 ms), Actuator for external motor brake
BRAKING TORQUE	Max. 100 % of rated operational current I _e , variable, DC - Main circuit
CABLE LENGTH	100 m, screened, maximum permissible, Motor feeder 200 m, screened, with motor choke, maximum permissible, Motor feeder 300 m, unscreened, with motor choke, maximum permissible, Motor feeder 150 m, unscreened, maximum permissible, Motor feeder
FUNCTIONS	4-quadrant operation possible
OUTPUT VOLTAGE (U₂)	230 V AC, 3-phase 240 V AC, 3-phase
DELAY TIME	< 10 ms, On-delay < 10 ms, Off-delay
NUMBER OF INPUTS (ANALOG)	2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)
NUMBER OF INPUTS (DIGITAL)	4 (parameterizable, 10 - 30 V DC)
RADIO INTERFERENCE CLASS	Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
NUMBER OF OUTPUTS	1

(DIGITAL)	
STARTING CURRENT - MAX	175 %, IH, max. starting current (High Overload), For 2.5 seconds every 600 seconds, Power section
NUMBER OF PHASES (INPUT)	3
NUMBER OF RELAY OUTPUTS	1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
NUMBER OF PHASES (OUTPUT)	3
POWER CONSUMPTION	446 W
RATED CONTROL SUPPLY VOLTAGE	10 V DC (Us, max. 10 mA)
SUPPLY FREQUENCY	50/60 Hz
LEAKAGE CURRENT AT GROUND IPE - MAX	6.9 mA
MAINS VOLTAGE - MIN	200 V
NOMINAL OUTPUT CURRENT I2N	46 A
NUMBER OF HW-INTERFACES (INDUSTRIAL ETHERNET)	0
NUMBER OF HW-INTERFACES (OTHER)	0
NUMBER OF HW-INTERFACES (PARALLEL)	0
NUMBER OF HW-INTERFACES (RS-232)	0
NUMBER OF HW-INTERFACES (RS-422)	0
NUMBER OF HW-INTERFACES (RS-485)	1
NUMBER OF HW-INTERFACES (SERIAL TTY)	0
NUMBER OF HW-INTERFACES (USB)	0
NUMBER OF INTERFACES (PROFINET)	0
NUMBER OF OUTPUTS (ANALOG)	1
OUTPUT AT LINEAR LOAD AT RATED OUTPUT VOLTAGE - MAX	11 kW
OUTPUT AT QUADRATIC LOAD AT RATED OUTPUT VOLTAGE - MAX	11 kW

OUTPUT FREQUENCY - MAX	500 Hz
OUTPUT FREQUENCY - MIN	0 Hz
SHORT-CIRCUIT PROTECTION (EXTERNAL OUTPUT CIRCUITS)	Type 1 coordination via the power bus' feeder unit, Main circuit
SUITABLE FOR	Branch circuits, (UL/CSA)
SWITCHING FREQUENCY	8 kHz, 4 - 24 kHz adjustable (audible), fPWM, Power section, Main circuit
RATED OPERATIONAL CURRENT (IE)	46 A at 150% overload (at an operating frequency of 16 kHz and an ambient air temperature of +50 °C)
RATED OPERATIONAL VOLTAGE	230 V AC, 3-phase 240 V AC, 3-phase
SHORT-CIRCUIT PROTECTION RATING	70 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
HEAT DISSIPATION AT CURRENT/SPEED	132 W at 25% current and 0% speed 162 W at 25% current and 50% speed 182 W at 50% current and 0% speed 219 W at 50% current and 50% speed 235 W at 50% current and 90% speed 342 W at 100% current and 0% speed 417 W at 100% current and 50% speed 455 W at 100% current and 90% speed
PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
:	