



Eaton 190312

Eaton Moeller® series PKZM0 Wiring module, for DILM17-M38, for screw terminals

□□□□

PRODUCT NAME	Eaton Moeller® series PKZM0 Accessory Wiring module
CATALOG NUMBER	190312
PRODUCT LENGTH/DEPTH	75 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.028 kg
CERTIFICATIONS	UL Category Control No.: NLRV CSA Class No.: 3211-05 CSA File No.: 165628 UL 508 CSA-C22.2 No. 14 IEC/EN 60947-4-1 CE CSA UL UL File No.: E36332
CATALOG NOTES	Cannot be combined with A-PKZ0... / U-PKZ0...

RATED OPERATIONAL VOLTAGE (UE) - MAX

690 VAC

10.10 TEMPERATURE RISE

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 CORROSION RESISTANCE

Meets the product standard's requirements.

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES

Meets the product standard's requirements.

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT

Meets the product standard's requirements.

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS

Meets the product standard's requirements.

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION

Meets the product standard's requirements.

10.2.5 LIFTING

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 MECHANICAL IMPACT

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 INSCRIPTIONS

Meets the product standard's requirements.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 CLEARANCES AND

Meets the product

DECLARATIONS OF CONFORMITY

[eaton-accessory-declaration-of-conformity-uk251183en.pdf](#)

□□□□□

[IL034054ZU](#)

□□

[eaton-manual-motor-starters-pkzm0-wiring-module-dimensions.eps](#)

[eaton-manual-motor-starters-pkzm0-wiring-module-3d-drawing.eps](#)

CREEPAGE DISTANCES	standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
MODEL	Direct circuit
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
HEAT DISSIPATION CAPACITY PDISS	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	32 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
SUITABLE FOR NUMBER OF POLES	3
PRODUCT CATEGORY	Accessories
CONNECTION	Screw
TYPE	Wiring set
RATED OPERATIONAL CURRENT (IE)	32 A

