Eaton 193223

Eaton xEnergy Basic LV systems Low voltage switchgear. Cable arrangement plinth for floor standing distribution board IP54, HxWxD=100x1200x400mm, grey

Eaton xEnergy Basic base element
193223
400 mm
100 mm
1200 mm
7.1 kg
RoHS conform



ТҮРЕ	Additional equipment
SURFACE FINISHING	With powder coating
COLOR	Light gray (RAL 7035) Gray
DEGREE OF PROTECTION	IP54
LOAD CAPACITY - MAX	300 kg
RAL-NUMBER	7035
SUITABLE FOR ENCLOSURE BUILDING LENGTH/DEPTH	400 mm
SUITABLE FOR ENCLOSURE BUILDING WIDTH	1200 mm
SUITABLE FOR LENGTH/DEPTH	400 mm
SUITABLE FOR WIDTH	1200 mm
MATERIAL	Sheet steel Steel
HOUSING MATERIAL	Sheet steel
MODEL	Base complete
MOUNTING METHOD	Floor standing distribution board
SUITABLE FOR	Cable patch
FUNCTIONS	Additional equipment
IMPACT STRENGTH	Other

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
:	



Eaton House 30 Pembroke Road Dublin 4, Eaton.com Follow us on social media to get the latest product and support information.









