

Eaton 197497

Eaton DA1 Frequency inverter, 400 V AC, 3-phase, 72 A, 37 kW, IP20/NEMA 0, Radio interference suppression filter, Additional PCB protection, DC link choke, FS5

PRODUCT NAME	Eaton DA1 Variable frequency drive
CATALOG NUMBER	197497
PRODUCT LENGTH/DEPTH	261 mm
PRODUCT HEIGHT	485 mm
PRODUCT WIDTH	234 mm
PRODUCT WEIGHT	18.2 kg
CERTIFICATIONS	CE IEC/EN61800-5 IEC/EN 61800-3 RoHS, ISO 9001 Certified by UL for use in Canada EAC RCM UkrSEPRO UL UL Category Control No.: NMMS, NMMS7 UL File No.: E172143 IEC/EN 61800-2 Safety: EN 61800-5-1: 2003 UL report applies to both US and Canada UL 508C CUL IEC/EN61800-3
CATALOG NOTES	The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.

PRODUCT CATEGORY	Variable frequency drives
FEATURES	Parameterization: drivesConnect Parameterization: drivesConnect mobile (App) Parameterization: Fieldbus Parameterization: Keypad
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.

INSTALLATION VIDEOS	Video PowerXL DA1
	eaton-da1-variable-frequency-drive-il040049zu.pdf
	eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf
	eaton-powerxl-da1-application-manual-mn04020006z-en-us.pdf
	eaton-powerxl-da1-installation-manual-mn04020005z-en-us.pdf
	eaton-frequency-inverter-dimensions-013.eps

10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Radio interference suppression filter Additional PCB protection DC link choke Internal DC link Control unit OLED display Brake chopper IGBT inverter PC connection Breaking resistance
CLIMATIC PROOFING	< 95 average relative humidity (RH), no condensation, no corrosion
CONNECTION TO SMARTWIRE-DT	Yes In conjunction with DX-NET-SWD1 SmartWire DT module
OPERATING MODE	U/f control Optional: Vector control with feedback (CLV)

	Speed control with slip compensation Sensorless vector control (SLV)
FRAME SIZE	FS5
ALTITUDE	Above 1000 m with 1 % derating per 100 m Max. 1000 m Max. 4000 m
ENVIRONMENTAL CLASS	3C2, 3S2 (Air quality)
APPLICATION IN DOMESTIC AND COMMERCIAL AREA PERMITTED	Yes
MAINS SWITCH-ON FREQUENCY	Maximum of one time every 30 seconds
APPLICATION IN INDUSTRIAL AREA PERMITTED	Yes
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE - MIN	-10 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MAX	50 °C
AMBIENT OPERATING TEMPERATURE AT 150% OVERLOAD - MIN	-10 °C
AMBIENT STORAGE TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
APPARENT POWER AT 400 V	49.88 kVA
APPARENT POWER AT 480 V	59.86 kVA
ASSIGNED MOTOR CURRENT IM AT 400 V, 50 HZ, 150% OVERLOAD	72 A
MOUNTING POSITION	Vertical
RELATIVE SYMMETRIC NET FREQUENCY TOLERANCE	10 %
RELATIVE SYMMETRIC NET VOLTAGE TOLERANCE	10 %
PROTECTION	Finger and back-of-hand proof, Protection against

	direct contact (BGV A3, VBG4)
RESOLUTION	0.1 Hz (Frequency resolution, setpoint value)
SWITCH-ON THRESHOLD FOR THE BRAKING TRANSISTOR	780 VDC
VOLTAGE RATING - MAX	480 VAC
COMMUNICATION INTERFACE	Modbus RTU DeviceNet, optional Ethernet IP, optional PROFIBUS, optional EtherCAT, optional CANopen® PROFINET, optional Modbus-TCP, optional SmartWire-DT, optional OP-Bus (RS485)
CONVERTER TYPE	U converter
DEGREE OF PROTECTION	IP20 NEMA Other
PROTOCOL	CAN Other bus systems DeviceNet TCP/IP EtherNet/IP MODBUS PROFINET IO PROFIBUS
ASSIGNED MOTOR CURRENT IM AT 440 - 480 V, 60 HZ, 150% OVERLOAD	65 A
SYSTEM CONFIGURATION TYPE	AC supply systems with earthed center point
ELECTROMAGNETIC COMPATIBILITY	1st and 2nd environments (according to EN 61800-3)
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	50 HP
BRAKING RESISTANCE	12 Ω
INPUT CURRENT ILN AT 150% OVERLOAD	76.4 A
BRAKING TORQUE	Adjustable to 100 % (DC) Max. 30 % MN, Standard - Main circuit Max. 100 % of rated operational current I _e with external braking resistor - Main circuit

CABLE LENGTH	<p>100 m, screened, maximum permissible cable length</p> <p>$C3 \leq 25$ m, maximum motor cable length</p> <p>$C2 \leq 5$ m, maximum motor cable length</p> <p>200 m, screened, with motor choke, maximum permissible cable length</p> <p>200 m, unscreened, with motor choke, maximum permissible cable length</p> <p>150 m, unscreened, maximum permissible cable length</p>
FUNCTIONS	4-quadrant operation possible
OUTPUT VOLTAGE (U2)	<p>480 V AC, 3-phase</p> <p>400 V AC, 3-phase</p>
NUMBER OF INPUTS (ANALOG)	2
NUMBER OF INPUTS (DIGITAL)	5
RADIO INTERFERENCE CLASS	<p>C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.</p> <p>Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments</p>
NUMBER OF OUTPUTS (DIGITAL)	2
STARTING CURRENT - MAX	200 %, I _H , max. starting current (High Overload), for 4 seconds every 40 seconds, Power section
NUMBER OF PHASES (INPUT)	3
NUMBER OF RELAY OUTPUTS	2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
NUMBER OF PHASES (OUTPUT)	3

POWER CONSUMPTION	925 W
RATED CONTROL SUPPLY VOLTAGE	10 V DC (Us, max. 10 mA)
EFFICIENCY	97.2 % (η)
RATED CONTROL VOLTAGE (UC)	24 V DC (external, max. 100 mA)
SUPPLY FREQUENCY	50/60 Hz
LEAKAGE CURRENT AT GROUND IPE - MAX	0.49 mA
MAINS VOLTAGE - MAX	480 V
MAINS VOLTAGE - MIN	380 V
NOMINAL OUTPUT CURRENT I2N	72 A
NUMBER OF HW-INTERFACES (INDUSTRIAL ETHERNET)	0
NUMBER OF HW-INTERFACES (OTHER)	0
NUMBER OF HW-INTERFACES (PARALLEL)	0
NUMBER OF HW-INTERFACES (RS-232)	0
NUMBER OF HW-INTERFACES (RS-422)	0
NUMBER OF HW-INTERFACES (RS-485)	1
NUMBER OF HW-INTERFACES (SERIAL TTY)	0
NUMBER OF HW-INTERFACES (USB)	0
NUMBER OF INTERFACES (PROFINET)	0
NUMBER OF OUTPUTS (ANALOG)	2
OUTPUT AT LINEAR LOAD AT RATED OUTPUT VOLTAGE - MAX	37 kW
OUTPUT AT QUADRATIC LOAD AT RATED OUTPUT VOLTAGE - MAX	37 kW
OUTPUT FREQUENCY - MAX	500 Hz
OUTPUT FREQUENCY - MIN	0 Hz
OUTPUT VOLTAGE - MAX	500 V
OVERLOAD CURRENT IL AT 150% OVERLOAD	105 A

SUITABLE FOR	Branch circuits, (UL/CSA)
SWITCHING FREQUENCY	8 kHz, 4 - 24 kHz adjustable (audible), fPWM, Power section, Main circuit
RATED OPERATIONAL VOLTAGE	480 V AC, 3-phase 400 V AC, 3-phase
SHORT-CIRCUIT PROTECTION RATING	100 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
RATED FREQUENCY - MAX	62 Hz
RATED FREQUENCY - MIN	48 Hz
RATED OPERATIONAL CURRENT (IE) AT 150% OVERLOAD	72 A
RATED OPERATIONAL POWER AT 380/400 V, 50 HZ, 3-PHASE	37 kW
SAFETY FUNCTION/LEVEL	STO (Safe Torque Off, SIL2, PLc Cat 2)
HEAT DISSIPATION AT CURRENT/SPEED	1050 W at 100% current and 90% speed 310 W at 25% current and 0% speed 310 W at 25% current and 50% speed 370 W at 50% current and 0% speed 460 W at 50% current and 50% speed 530 W at 50% current and 90% speed 720 W at 100% current and 0% speed 930 W at 100% current and 50% speed

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

