

Eaton 199447

Eaton DC1 Variable frequency drive, 400 V AC, 3-phase, 39 A, 18.5 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Additional PCB protection, UV resistant, FS4

PRODUCT NAME	Eaton DC1 Variable frequency drive
CATALOG NUMBER	199447
PRODUCT LENGTH/DEPTH	275 mm
PRODUCT HEIGHT	360 mm
PRODUCT WIDTH	240 mm
PRODUCT WEIGHT	9.5 kg
CERTIFICATIONS	UL Category Control No.: NMMS, NMMS7 CUL CE IEC/EN 61800-5-1 RoHS, ISO 9001 Certified by UL for use in Canada UL RCM EAC CSA-C22.2 No. 14 IEC/EN 61800-2 UL Listed IEC/EN 61800-3 CE marking IEC/EN61800-5 UkrSEPRO UL report applies to both US and Canada UL 508C UL File No.: E172143
CATALOG NOTES	<ul style="list-style-type: none">• Environmental class: 3C3, 3S3• Overload cycle for 60 s every 600 s

- For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz

	Parameterization: Keypad Parameterization: Fieldbus
FEATURES	Parameterization: drivesConnect mobile (App) Parameterization: drivesConnect
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL	Does not apply, since the

IMPACT	entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	IGBT inverter Internal DC link Control unit Radio interference suppression filter Brake chopper UV resistance 7-digital display assembly PC connection Breaking resistance Additional PCB protection
CLIMATIC PROOFING	< 95 average relative humidity (RH), no condensation, no corrosion
CONNECTION TO SMARTWIRE-DT	No
OPERATING MODE	U/f control Sensorless vector control (SLV) BLDC motors Synchronous reluctance motors

	PM motors Speed control with slip compensation
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	2000 V
FRAME SIZE	FS4
ALTITUDE	Above 1000 m with 1 % derating per 100 m Max. 4000 m
APPLICATION IN DOMESTIC AND COMMERCIAL AREA PERMITTED	Yes
MAINS SWITCH-ON FREQUENCY	Maximum of one time every 30 seconds
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-20 °C
MAINS VOLTAGE - MAX	480 V
OUTPUT VOLTAGE - MAX	500 V
RELATIVE SYMMETRIC NET FREQUENCY TOLERANCE	10 %
RELATIVE SYMMETRIC NET VOLTAGE TOLERANCE	10 %
AMBIENT STORAGE TEMPERATURE - MAX	60 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
APPARENT POWER AT 400 V	15.6 kVA
APPARENT POWER AT 480 V	18.72 kVA
APPLICATION IN INDUSTRIAL AREA PERMITTED	Yes
PRODUCT CATEGORY	Variable frequency drives
PROTECTION	Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
RESOLUTION	0.1 Hz (Frequency resolution, setpoint value)
SWITCH-ON THRESHOLD FOR THE BRAKING	780 VDC

TRANSISTOR	
VOLTAGE RATING - MAX	240 V
MOUNTING POSITION	Vertical
OVERVOLTAGE CATEGORY	III
COMMUNICATION INTERFACE	OP-Bus (RS485), built in SmartWire-DT, optional Modbus RTU, built in CANopen®, built in
CONVERTER TYPE	U converter
DEGREE OF PROTECTION	NEMA 4X IP66
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	25 HP
BRAKING RESISTANCE	22 Ω
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
INPUT CURRENT ILN AT 150% OVERLOAD	44.1 A
MAINS CURRENT DISTORTION	120 %
PROTOCOL	MODBUS CAN EtherNet/IP Other bus systems
OVERLOAD CURRENT IL AT 150% OVERLOAD	58.5 A
RATED FREQUENCY - MAX	62 Hz
RATED FREQUENCY - MIN	48 Hz
RATED OPERATIONAL POWER AT 380/400 V, 50 HZ, 3-PHASE	18.5 kW
ASSIGNED MOTOR CURRENT IM AT 400 V, 50 HZ, 150% OVERLOAD	39 A
ASSIGNED MOTOR CURRENT IM AT 440 - 480 V, 60 HZ, 150% OVERLOAD	39 A
SYSTEM CONFIGURATION TYPE	AC supply systems with earthed center point
BRAKING CURRENT	≤ 0.6 A (max. 6 A for 120 ms), Actuator for external

	motor brake
ELECTROMAGNETIC COMPATIBILITY	1st and 2nd environments (according to EN 61800-3)
BRAKING TORQUE	Max. 100 % of rated operational current I_e , variable, DC - Main circuit
CABLE LENGTH	<p>$C3 \leq 25$ m, maximum motor cable length</p> <p>200 m, screened, with motor choke, maximum permissible cable length</p> <p>150 m, unscreened, maximum permissible cable length</p> <p>100 m, screened, maximum permissible cable length</p> <p>300 m, unscreened, with motor choke, maximum permissible, Motor feeder</p> <p>$C2 \leq 5$ m, maximum motor cable length</p>
FUNCTIONS	4-quadrant operation possible
OUTPUT VOLTAGE (U2)	<p>400 V AC, 3-phase</p> <p>480 V AC, 3-phase</p>
DELAY TIME	<p>< 10 ms, On-delay</p> <p>< 10 ms, Off-delay</p>
NUMBER OF INPUTS (ANALOG)	2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)
NUMBER OF INPUTS (DIGITAL)	4 (parameterizable, 10 - 30 V DC)
RADIO INTERFERENCE CLASS	<p>Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments</p> <p>C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.</p>
NUMBER OF OUTPUTS (DIGITAL)	1
STARTING CURRENT - MAX	175 % I_H
NUMBER OF PHASES (INPUT)	3

NUMBER OF RELAY OUTPUTS	1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
NUMBER OF PHASES (OUTPUT)	3
POWER CONSUMPTION	728 W
RATED CONTROL SUPPLY VOLTAGE	10 V DC (Us, max. 10 mA)
EFFICIENCY	97 % (η)
SUPPLY FREQUENCY	50/60 Hz
LEAKAGE CURRENT AT GROUND IPE - MAX	12.9 mA
MAINS VOLTAGE - MIN	380 V
NOMINAL OUTPUT CURRENT I2N	39 A
NUMBER OF HW-INTERFACES (INDUSTRIAL ETHERNET)	0
NUMBER OF HW-INTERFACES (OTHER)	0
NUMBER OF HW-INTERFACES (PARALLEL)	0
NUMBER OF HW-INTERFACES (RS-232)	0
NUMBER OF HW-INTERFACES (RS-422)	0
NUMBER OF HW-INTERFACES (RS-485)	1
NUMBER OF HW-INTERFACES (SERIAL TTY)	0
NUMBER OF HW-INTERFACES (USB)	0
NUMBER OF INTERFACES (PROFINET)	0
NUMBER OF OUTPUTS (ANALOG)	1
OUTPUT AT LINEAR LOAD AT RATED OUTPUT VOLTAGE - MAX	18.5 kW
OUTPUT AT QUADRATIC LOAD AT RATED OUTPUT VOLTAGE - MAX	18.5 kW
OUTPUT FREQUENCY - MAX	500 Hz
OUTPUT FREQUENCY - MIN	0 Hz
SHORT-CIRCUIT	Type 1 coordination via

PROTECTION (EXTERNAL OUTPUT CIRCUITS)	the power bus' feeder unit, Main circuit
SUITABLE FOR	Branch circuits, (UL/CSA)
SWITCHING FREQUENCY	8 kHz, 4 - 24 kHz adjustable (audible), fPWM, Power section, Main circuit
RATED OPERATIONAL CURRENT (IE)	39 A at 150% overload (at an operating frequency of 6 kHz and an ambient air temperature of +40 °C)
RATED OPERATIONAL VOLTAGE	480 V AC, 3-phase 400 V AC, 3-phase
SHORT-CIRCUIT PROTECTION RATING	60 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
HEAT DISSIPATION AT CURRENT/SPEED	154 W at 25% current and 0% speed 165 W at 25% current and 50% speed 209 W at 50% current and 50% speed 214 W at 50% current and 0% speed 219 W at 50% current and 90% speed 309 W at 100% current and 0% speed 338 W at 100% current and 90% speed 375 W at 100% current and 50% speed

INSTALLATION VIDEOS

[Video PowerXL DA1](#)

MCAD MODEL

[e3_s4_ip66_ohne_bedienelementen.dwg](#)

[e3_s4_ip66_ohne_bedienelementen.stp](#)

[eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf](#)

[eaton-frequency-inverter-dc1-dimensions-008.eps](#)

[How does the internal motor protection work?](#)

[DX-COM-STICK3 Connection](#)

[The OP System Bus - Parameterizing - Control](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com
© 2025

Follow us on social media to get the latest product and support information.

