

Eaton 199465

Eaton Moeller® series PKZM0 Wiring set, For DOL Starter, Push in terminals PKZM0-XDM32-PI

PRODUCT NAME	Eaton Moeller® series PKZM0 Accessory Wiring module
CATALOG NUMBER	199465
PRODUCT LENGTH/DEPTH	42 mm
PRODUCT HEIGHT	63.7 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.058 kg
COMPLIANCES	CE Marked RoHS conform
CERTIFICATIONS	UL Category Control No.: NLRV CSA Class No.: 3211-05 CSA File No.: 165628 UL 508 CSA-C22.2 No. 14 IEC/EN 60947-4-1 CE CSA UL UL File No.: E36332
CATALOG NOTES	Suitable for PKZM0...-PI / SPI32 and contactor DILM8-11...38-11-PI

RATED OPERATIONAL VOLTAGE (UE) - MAX	690 VAC
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF	Does not apply, since the

ECAD MODEL	ETN.PKZM0-XDM32-PI.edz
	eaton-manual-motor-starters-motorsarter-msc-d-dol-starter-dimensions-002.eps

PROTECTION OF ASSEMBLIES	entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
MODEL	Direct circuit
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
SUITABLE FOR NUMBER OF POLES	3
PRODUCT CATEGORY	Accessories
CONNECTION	Push in terminals
TYPE	Wiring set
RATED OPERATIONAL CURRENT (IE)	32 A

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

