Eaton 200FEE

Eaton Bussmann series high speed British standard fuse, Double barrel, 200A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

PRODUCT NAME	Eaton Bussmann series high speed british standard fuse	
CATALOG NUMBER	200FEE	
UPC	051712832182	
PRODUCT LENGTH/DEPTH	100 mm	
PRODUCT HEIGHT	22 mm	
PRODUCT WIDTH	187 mm	
PRODUCT WEIGHT	89.6 g	
COMPLIANCES	CE Marked RoHS Compliant	
CERTIFICATIONS	IEC Rated UL Recognized Designed and tested to BS88 part 4 IEC 60269-4	



AMPERAGE RATING	200 A	
BREAKING CAPACITY	200 kA	
FUSE INDICATOR	None	
INSULATED METAL GRIPPING LUGS (IMGL)	No	
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)	
VOLTAGE TYPE	AC/DC	
RATED SWITCHING CAPACITY	200 kA	
RATED VOLTAGE AC	690 V	
RATED VOLTAGE DC	500 V	
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	71 mm	
MOUNTING DIMENSION	M8	
CURRENT TYPE	AC/DC	
CLASS	Class aR	
CLEARING (I2T)	7100 at 415 V, 11400 at 660 V	
WATT LOSSES	52 W	
FUSE SHAPE	Offset dual barrel bolted tags	
PRE ARC (I2T)	1900	
COLOR	None	
INTERRUPT RATING	200 kA RMS Sym, 50 kA at 500 Vdc	
CONNECTION	Blade end x blade end	
CONSTRUCTION SIZE	Other	
MOUNTING METHOD	Stud	
PACKAGING TYPE	Standard	
VOLTAGE RATING	690 V (IEC), 700 V (UL)	
ТҮРЕ	Fuse	
APPLICATION	Semiconductor, DC Common bus, DC drives, power converters/rectifiers	
FUSE TYPE	FEE	
SUITABLE FOR	EC-600 Trip indicator kit (indicator + clips) TI700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor	

DECLARATIONS OF CONFORMITY

eaton-high-speed-britishstandard-fuse-declarationof-conformityuk250922en.pdf FUSE SYSTEM (ACCORDING TO IEC 60269)

Other

PROJECT N	IAME:
-----------	-------

PROJECT NUMBER:

PREPARED BY:

:



Eaton House 30 Pembroke Road Dublin 4, Eaton.com Follow us on social media to get the latest product and support information.









