

Eaton 216536

Eaton Moeller® series M22 Surface mounting enclosure, yellow, 1 mounting location

PRODUCT NAME	Eaton Moeller® series M22 Accessory Surface mounting enclosure
CATALOG NUMBER	216536
PRODUCT LENGTH/DEPTH	80 mm
PRODUCT HEIGHT	56 mm
PRODUCT WIDTH	72 mm
PRODUCT WEIGHT	0.136 kg
CERTIFICATIONS	CSA File No.: 012528 CE CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 UL UL Category Control No.: NKCR IEC/EN 60947-5 UL File No.: E29184 UL 508 CSA CSA Class No.: 3211-03

10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.

MCAD MODEL	eaton-aufbaueghaeuse-gr1-drawing.dwg
	eaton-aufbaueghaeuse-gr1-3d-model.stp
	IL04716003Z
	eaton-operating-surface-mounting-m22-accessory-dimensions-003.eps
/	RMO small E-Stop emergency-stop button

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	High-grade steel screws
CONNECTION TO SMARTWIRE-DT	No
ENCLOSURE MATERIAL	Plastic
ENCLOSURE TYPE	Surface mounting housing
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
FORCE FOR POSITIVE OPENING - MIN	0 N
NUMBER OF COMMAND POSITIONS	1
NUMBER OF LOCATIONS	1
ENCLOSURE COLOR	Yellow
MATERIAL QUALITY	Other
OPENING DIAMETER	22.5 mm
RAL-NUMBER	1004
DEGREE OF PROTECTION	NEMA 13 IP67/IP69K
KNOCKOUTS	2 x M16 (cable entry knockouts at the rear) 1 x M20 (cable entry knockout at the top) 2 x M20/25 (cable entry knockout at the side, 1 x each side)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

