

Eaton 260182

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, red-yellow for emergency switching off, size 3

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	260182
PRODUCT LENGTH/DEPTH	100 mm
PRODUCT HEIGHT	230 mm
PRODUCT WIDTH	120 mm
PRODUCT WEIGHT	1.434 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	IEC60947 CSA certified UL (Category Control Number DIHS) CSA (Class No. 1437-01) CSA (File No. 22086) CSA-C22.2 No. 5-09 UL listed UL489 UL (File No. E140305) CE marking

USED WITH	NZM3(-4), PN3(-4), N(S)3(-4)
FEATURES	Lockable Red-yellow for emergency switching off
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.

DECLARATIONS OF CONFORMITY	DA-DC-03 NZM3
	IL01208007Z
	eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-006.eps
	eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-003.eps
	eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-004.eps
	eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Red
FITTED WITH:	Padlock
FRAME	NZM3
SUITABLE FOR	Switch disconnecter Power circuit breaker Emergency stop
COVER/DOOR TYPE	Door interlock not defeated in the locked OFF position. Door interlock can be modified in the unlocked ON position Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door can be opened in OFF
LOCK NUMBER	Double lockable
LOCKING FACILITY	Lockable on the handle on the switch using up to 3 padlocks With door interlock

TYPE	<ul style="list-style-type: none">• Accessory• Door coupling rotary handle
SPECIAL FEATURES	<ul style="list-style-type: none">• Door coupling rotary handle for operating the switch through a closed control panel door• External warning plate/designation label can be clipped on.• Complete including rotary drive and coupling parts• Extension shaft additionally required.
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
: