

Eaton 266616

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, lockable on the handle+switch

PRODUCT NAME	Eaton Moeller series NZM operating element
CATALOG NUMBER	266616
PRODUCT LENGTH/DEPTH	230 mm
PRODUCT HEIGHT	130 mm
PRODUCT WIDTH	230 mm
PRODUCT WEIGHT	1.934 kg
COMPLIANCES	UL/CSA IEC RoHS conform
CERTIFICATIONS	UL489 CSA (File No. 22086) CE marking UL (File No. E140305) CSA-C22.2 No. 5-09 UL (Category Control Number DIHS) UL listed CSA certified CSA (Class No. 1437-01) IEC60947

USED WITH	NZM4(-4), N(S)4(-4)
FEATURES	Lockable Standard: black / gray
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

IL01210003Z	
eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-011.eps eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-007.eps eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-005.eps	

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
COLOR	Black
FITTED WITH:	Padlock
FRAME	NZM4
SUITABLE FOR	Switch disconnecter Power circuit breaker
COVER/DOOR TYPE	Door interlock can be modified in the unlocked ON position Door can be opened in OFF Door interlock not defeated in the locked OFF and ON positions Door interlock can be modified such that it can be defeated from the outside using a screwdriver
LOCK NUMBER	Double lockable
LOCKING FACILITY	Modifiable on handle in I position as well Lockable on the handle on the switch using up to 3 padlocks With door interlock
TYPE	Accessory Door coupling

	rotary handle
SPECIAL FEATURES	Door coupling rotary handle for operating the switch through a closed control panel door External warning plate/designation label can be clipped on. Complete including rotary drive and coupling parts Extension shaft additionally required.
DEGREE OF PROTECTION / NEMA ENCLOSURE TYPE	IP66 4X. 12

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
: