

00000

Eaton 267075

Eaton Moeller series NZM - Molded Case Circuit Breaker. Box terminal, 4p, up to 160 A, 1

0000	
PRODUCT NAME	Eaton Moeller series NZM connection type
CATALOG NUMBER	267075
PRODUCT LENGTH/DEPTH	13 mm
PRODUCT HEIGHT	24.5 mm
PRODUCT WIDTH	16.6 mm
PRODUCT WEIGHT	0.096 kg
COMPLIANCES	IEC RoHS conform



0000	
USED WITH	NZM1(-4), PN1(-4), N(S)1(- 4)
AMPERAGE RATING	□ 160 A
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.

00	
MCAD MODEL	nzm1_xkc.stp
00000	eaton-cirucit-breaker- switch-disconnector- nzmb-il01203004z.pdf

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	ls the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	ls the panel builder's responsibility.
10.9.2 POWER- FREQUENCY ELECTRIC STRENGTH	ls the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	ls the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	ls the panel builder's responsibility.
FRAME	NZM1
SUITABLE FOR	Copper cable Four-pole
NUMBER OF POLES	Four-pole
TERMINAL CAPACITY (COPPER STRIP)	2 segments of 9 mm x 0.8 mm - 9 segments of 9 mm x 0.8 mm
MODEL	Other
ТҮРЕ	AccessoryBox terminal
TERMINAL CAPACITY (STRANDED CABLE)	10 mm ² - 70 mm ² (1x) 12 - 2/0 AWG/kcmil (1x) 6 mm ² - 25 mm ² (2x)

0000:	
0000:	
000:	
00:	



Baton House 30 Pembroke Road Dublin 4, BBB Eaton.com











