

Eaton 269512

Eaton DX Main choke, three-phase, 550 V + 0% (50/60 Hz), V AC, 200 A, 0.09 mH

PRODUCT NAME	Eaton DX Mains choke
CATALOG NUMBER	269512
PRODUCT LENGTH/DEPTH	155 mm
PRODUCT HEIGHT	202 mm
PRODUCT WIDTH	270 mm
PRODUCT WEIGHT	14.9 kg
CERTIFICATIONS	CSA-C22.2 No. 14 IEC/EN61800-3 UL UL report applies to both US and Canada VDE 0570 Part 2-20/2001-04 IEC/EN61800-5 CE UL Category Control No.: XPTQ2, XPTQ8 Certified by UL for use in Canada IEC/EN 61558-2-20-2000 UL 508C CSA UL File No.: E167225

USED WITH	DA1
PRODUCT CATEGORY	Accessories
SUITABLE AS	Net reactance coil
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.

DECLARATIONS OF CONFORMITY	eaton-accessory-declaration-of-conformity-uk251055en.pdf
	IL00906003Z
	eaton-powerxl-da1-installation-manual-mn04020005z-en-us.pdf
	eaton-regulating-equipment-options-dx-main-choke-dimensions-011.eps
	eaton-regulating-equipment-options-dx-main-choke-3d-drawing-002.eps

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	PE stud Connection lugs
FREQUENCY RATING	50-60 Hz
ALTITUDE	Max. 5000 m with current reduction Max. 1000 m
AMBIENT OPERATING TEMPERATURE - MAX	40 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
RATED CURRENT (ITH) AT RATED VOLTAGE DC - MAX	200 A
RATED FREQUENCY - MAX	60 Hz
RATED FREQUENCY - MIN	50 Hz
RATED INDUCTANCE	0.09 mH
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
AMBIENT STORAGE TEMPERATURE - MIN	-25 °C
BORE DIAMETER	11 mm
EQUIPMENT HEAT DISSIPATION, CURRENT-	154 W

DEPENDENT PVID	
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
NUMBER OF PHASES	3
MOUNTING POSITION	Free surrounding areas > 50 mm Standing vertically Suspended horizontally
CONNECTION LUG	Cu 25 x 5 mm ²
DUTY FACTOR	100 %
DEGREE OF PROTECTION	IP00 NEMA Other
RELATIVE SHORT-CIRCUIT VOLTAGE	2.5 %
INSULATION CLASS	B
RATED OPERATIONAL VOLTAGE (UE) - MAX	550 V
RATED OPERATIONAL CURRENT (IE) - MAX	200 A
RATED OPERATIONAL CURRENT (IE) - MIN	200 A
RESONANCE FREQUENCY	0 Hz
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE DETAILS	-25 - 40 °C (up to 70 °C with current derating)
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	200 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
VOLTAGE RATING - MAX	480 V
VOLTAGE SAG UK	2.5 %
VIBRATION RESISTANCE	10 - 55 Hz, 0.35 mm 0 - 150 Hz, 1 g
PERMISSIBLE CONNECTION VOLTAGE	Max. 550 V AC (50/60 Hz)
SHOCK RESISTANCE	3 shocks Shock duration: 11 ms
SUITABLE FOR	Branch circuits, (UL/CSA)
SWITCHING FREQUENCY	0 kHz
TIGHTENING TORQUE	10 Nm, Screw terminals

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com
© 2025

Follow us on social media to get the latest product and support information.

