



□□□□□

Eaton 271529

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, box size HxWxD=375x250x225mm, for NZM size 3, TVDR

□□□□

PRODUCT NAME	Eaton xEnergy Safety Ci MCCB enclosure
CATALOG NUMBER	271529
PRODUCT LENGTH/DEPTH	225 mm
PRODUCT HEIGHT	375 mm
PRODUCT WIDTH	250 mm
PRODUCT WEIGHT	6.296 kg
COMPLIANCES	IEC RoHS conform

□□□□	
USED WITH	xEnergy Safety Ci NZM2(-4), PN2(-4), N(S)2(-4)
SPECIAL FEATURES	With door coupling rotary handle Complete with all required functional parts
TYPE	xEnergy Safety Ci
FITTED WITH:	Transparent cover Red-yellow for emergency switching off
FRAME	NZM2
ENCLOSURE	CI43-200
ACCESSORY/SPARE PART TYPE	Others
DEGREE OF PROTECTION	IP65 Other
ENCLOSURE MATERIAL	Plastic
RATED UNINTERRUPTED CURRENT (IU) AT MAX. CROSS SECTION	≤ 200 A
TERMINAL FOR RETROFITTING OF 5TH CONDUCTOR (NEUTRAL CONDUCTOR)	K50/1, K95/1N/BR, K150/1/BR, K240/1/BR
LOCKING FACILITY	Lockable in the 0 position using up to 3 padlocks on the handle and/or switch each. Additionally with cover interlock.
MODEL	Surface mounting
NUMBER OF POLES	Three-pole/Four-pole
SUITABLE FOR	Emergency stop

□□□□:
□□□□:
□□□:
□□:

□□	
MCAD MODEL	nzm2_xci43_tvdvr.dwg nzm2_xci43_tvdvr.stp
□□□□	eaton-xenergy-safety-ci-subway-line-success-story-en-us.pdf eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf
□□□□	eaton-xenergy-ci-safety-catalog-ca015006en-en-us.pdf
□□	eaton-circuit-breaker-enclosure-xenergy-safety-ci-lv-systems-dimensions-006.eps