



□□□□□

Eaton 40071352413

Eaton monitoring interfaces CG-S module V-
CG-SUW monitoring module (without
packing)

□□□□

PRODUCT NAME	Eaton monitoring interfaces CG-S module
CATALOG NUMBER	40071352413
PRODUCT LENGTH/DEPTH	242 mm
PRODUCT HEIGHT	28 mm
PRODUCT WIDTH	40 mm
PRODUCT WEIGHT	0.14 kg
CERTIFICATIONS	CE

□□□□

□□

POWER	400 W
MONITORING EQUIPMENT	Other
WIRING SYSTEM	Standby switching
NOMINAL VOLTAGE - MAX	240 V
NOMINAL VOLTAGE - MIN	220 V
PROTECTION CLASS	I
NOMINAL VOLTAGE RANGE DC - MAX	275 V
NOMINAL VOLTAGE RANGE DC - MIN	176 V
ADDITIONAL DATA LINE NEEDED	No
AMBIENT TEMPERATURE - MAX	60 °C
AMBIENT TEMPERATURE - MIN	-20 °C
CONNECTION TERMINALS (IN)	2.5 mm ²
CONNECTION TERMINALS (OUT)	2.5 mm ²
ENEC CERTIFIED	Yes
HOUSING COLOR	White
HOUSING MATERIAL	Sheet Steel
MAXIMAL NUMBER OF MONITORED LUMINAIRES PER CIRCUIT	20
REVERSE-POLARITY PROTECTED TERMINALS (IN)	Yes
SLI-TECHNOLOGY	No
IOK (NORMAL CURRENT DRAWN) LEVEL 1	47 mA
I NOT OK (FAILURE CURRENT DRAWN) LEVEL 1	28 mA
PRODUCT BRANDING	Eaton
DEGREE OF PROTECTION (IP)	IP20
MAXIMAL PERMISSIBLE TEST POINT TEMPERATURE	75 °C
LINE LENGTH - MAX	50 m
OPERATING FREQUENCY	60 Hz
STANDBY POWERLOSS AT	0.8 W

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

□□:



□□□□
Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2025 □□ □□□□□□

Follow us on social media to get the latest product and support information.

