Eaton 500RJ31-8

Eaton Bussmann series low voltage british standard fuse, 500A, AC 415 V, V88/J, 49 \times 131 mm, gU, 92mm fixing centres

Eaton Bussmann series low voltage british standard fuse
500RJ31-8
131 mm
50 mm
50 mm
411 g
CE Marked RoHS Compliant
BS IEC 60269 EAC



AMPERAGE RATING	500 A
FITTED WITH:	Slotted tags
CURRENT TYPE	AC
MOUNTING DIMENSION	Other
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	92 mm
BREAKING CAPACITY	80 kA
RATED SWITCHING CAPACITY	80 kA
RATED VOLTAGE AC	415 V
CLASS	Class gG/gL
FUSE TYPE	RJ31
UTILIZATION CATEGORY	gU (utility/distribution protection)
COLOR	None
INTERRUPT RATING	80 kAIC
FUSE INDICATOR	None
INSULATED METAL GRIPPING LUGS (IMGL)	No
CONNECTION	Bolt-on
CONSTRUCTION	BS88/J
CONSTRUCTION SIZE	J
FUSE SHAPE	Dual slotted bolted tags
VOLTAGE TYPE	AC
VOLTAGE RATING	415 V
ТҮРЕ	Fuse
APPLICATION	feeder pillars
FUSE SYSTEM (ACCORDING TO IEC	Fuse system E

60269)

DECLARATIONS OF CONFORMITY

eaton-low-voltage-britishstandard-fuse-declarationof-conformityuk251033en.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
:	



Eaton House 30 Pembroke Road Dublin 4, Eaton.com

Follow us on social media to get the latest product and support information.









