

Eaton 5PX3000IRT3U

5PX UPS 3000 VA 2700 W C20
(8) C13 (1) C19 / 3U

5PX UPS	
5PX3000IRT3U	
UPC	743172035967
/	441 mm
	130.7 mm
	497 mm
	37.33 kg
	CE TUV
	IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 CE EAC cTUVus



- (AVR)
-
-
- 0.9
-
- 4 EBM
-
-
- 1

- VMware
Hyper-V Citrix
Xen Redhat
- Intelligent
Power Manager
- 1 USB + 1

/
3U
482.6 19
/
/
3000 VA
2700 W

-
-
- (2)
-
- USB
-
- (2) IEC-IEC
-
-

- 70 Hz
- 47 Hz
C20
1.8m

	230V (200/208/220/230/240V)
	50-60 Hz
	47-70 Hz 50 Hz 56.5-70 Hz 60 Hz 40 Hz
	(8) C13 (1) C19
C13	8
C19	1
	230V
	230V (200/208/220/230/240V)
	1
	AC
	\$row.attributeValue.cdata
	ABM
	12 V/9 Ah
	- ()
	10 min
	• USB HID • (RS232) • 1 / • 2 RJ
	1
	LCD
	3000 m
BTU	277
	1 <40 dB
	0-90%
	0-90%
-	294 V

-	150 V
-	240 V
-	200 V
-	60 Hz
-	50 Hz
	6
	97
	160-294 V 150 V-294 V
	4
	50/60 Hz
	0.9
	230 V (+6%/-10%)
	1
	1
	3

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

