Eaton 9PXMSPPM

Eaton 9PXM 4 kVA / 3.6 kW split-phase power module

PRODUCT NAME	Eaton 9PXM split-phase power module
CATALOG NUMBER	9PXMSPPM
UPC	743172091437
PRODUCT LENGTH/DEPTH	8.5 in
PRODUCT HEIGHT	23 in
PRODUCT WIDTH	6 in
PRODUCT WEIGHT	22.5 lb
COMPLIANCES	TAA Compliant FCC Compliant
CERTIFICATIONS	IEC Rated cULus Listed

Powering Business Worldwide

□□□□

TOPOLOGY	Online/Double-conversion
COLOR	Black/silver
PACKAGE CONTENTS	9PXMSPPM 9PXM 4000VA 3600W Split-Phase Power Module
INTERNAL BYPASS	Yes
HOT SWAP POWER	Yes
INPUT CONNECTION	Hardwired
INPUT NOMINAL VOLTAGE	110V/220V, 120V/208V, 120V/240V, 127V/220V
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>0.99 typical
NUMBER OF OUTPUTS HARDWIRED	1
OUTPUT WAVEFORM	True sine wave
VOLTAGE	120/208V
OUTPUT NOMINAL VOLTAGE	110V/220V, 120V/208V, 120V/240V, 127V/220V
FEED TYPE	1
RUNTIME GRAPH	View runtime graph
BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
RELATIVE HUMIDITY	5-95% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
ACCESSORY CLASS	UPS Accessories
ACCESSORY TYPE	Power Module
MAX NUMBER OF BATTERY PACKS	8
OUTPUT FREQUENCY	60 Hz
OUTPUT POWER FACTOR	0.9

□□

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□