



□□□□

Eaton ACE10 30

Eaton Crouse-Hinds series ACE10 variable frequency drive, J disconnect fuse type, ABB ACS880-M04 Series drive, Size 2 enclosure, 42A input, 30 HP, Copper-free aluminum, 60A max. disconnect rating, 50A max. output, T4A, 22 kW

□□□□

PRODUCT NAME	Eaton Crouse-Hinds series ACE10 variable frequency drive
CATALOG NUMBER	ACE10 30
UPC	662276247109
PRODUCT LENGTH/DEPTH	46.31 in
PRODUCT HEIGHT	15.74 in
PRODUCT WIDTH	25.15 in
PRODUCT WEIGHT	552 lb



Powering Business Worldwide

□□□□

AREA CLASSIFICATION	Hazardous/Classified Locations
DISCONNECT FUSE TYPE	J
DRIVE TYPE	ABB ACS880-M04 Series
HORSEPOWER	30 hp
MATERIAL	Copper-free aluminum
DISCONNECT RATING - MAX	60A
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2
NEMA RATING	3 4X 7
ENCLOSURE SIZE	Size 2
TEMPERATURE RATING	T4A
WATTAGE	22 kW
INPUT CURRENT	42 A
OUTPUT CURRENT - MAX	50 A

□□□□:

□□□□:

□□□:

□□:

□□

	IF 1616 - Flange Gasket Replacement Kit
□□□□□	IF 1689 - ACE Variable Frequency Drive System
	IF 1619 - ACE10 Variable Frequency Drive System
□□□□□□□□	Eaton Specification Sheet - ACE10 30 ACE Series Explosionproof Variable Frequency Drives
□□□□	ACE10 Series Explosionproof Variable Frequency Drives brochure
□□□□	ACE10 Series Explosionproof Variable Frequency Drives catalog page
□□□□	ACE10 Explosionproof Variable Frequency Drives Canadian certification (pending) ACE10 Explosionproof Variable Frequency Drives UL certification



□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

□□□□□□□□□□□□□□□□□□□□□□□□



© 2026 □□ □□□□□□□□