Eaton CD80

Eaton Bussmann series low voltage british standard fuse, 80A, AC 500 V, V88/B1, 21 \times 126 mm, gL/gG

PRODUCT NAME	Eaton Bussmann series low voltage british standard fuse
CATALOG NUMBER	CD80
UPC	051712838825
PRODUCT LENGTH/DEPTH	127 mm
PRODUCT HEIGHT	21 mm
PRODUCT WIDTH	21 mm
PRODUCT WEIGHT	80.2 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	BS88 IEC 60269 EAC



AMPERAGE RATING	80 A
FITTED WITH:	Centre bolted tags
FUSE SIZE	BS88/B1
CURRENT TYPE	AC
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	111 mm
BREAKING CAPACITY	80 kA
RATED SWITCHING CAPACITY	80 kA
RATED VOLTAGE AC	500 V
CLASS	Class gG/gL
FUSE TYPE	CD
UTILIZATION CATEGORY	gL/gG (cable protection/equipment protection)
COLOR	None
INTERRUPT RATING	80 kAIC
FUSE INDICATOR	None
INSULATED METAL GRIPPING LUGS (IMGL)	No
WATT LOSSES	7.2 W
CONNECTION	111 mm fixing centre
CONSTRUCTION	BS88/B1
CONSTRUCTION SIZE	B1
FUSE SHAPE	Center bolted tags
VOLTAGE TYPE	AC
VOLTAGE RATING	500 V
ТҮРЕ	Fuse
APPLICATION	general industrial applications
FUSE SYSTEM (ACCORDING TO IEC 60269)	Fuse system E

DECLARATIONS OF CONFORMITY

eaton-low-voltage-britishstandard-fuse-declarationof-conformityuk250891en.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
:	



Eaton House 30 Pembroke Road Dublin 4, Eaton.com

Follow us on social media to get the latest product and support information.









