



□□□□□

Eaton EIDA3030 S752 S784

Eaton Crouse-Hinds series EID disconnect switch, 30A, With switch, Non-fused, 5 HP/10 HP/20 HP/30 HP, Copper-free aluminum, Auxiliary contact (single block), external epoxy powder coat finish, 240-600 Vac/250 Vdc

□□□□

PRODUCT NAME	Eaton Crouse-Hinds series EID disconnect switch
CATALOG NUMBER	EIDA3030 S752 S784
UPC	662276698703
PRODUCT LENGTH/DEPTH	10.47 in
PRODUCT HEIGHT	12.47 in
PRODUCT WIDTH	9.65 in
PRODUCT WEIGHT	36 lb

0000	
SPECIAL FEATURES	Auxiliary contact (single block), external epoxy powder coat finish
AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 2 Class II, Division 1 Class I, Zone 1 Class I, Zone 2 Class I, Division 1 Class III
NEMA RATING	9 3 4X 7 4 3R
AMPERAGE RATING	30A
ENCLOSURE TYPE	With switch
FUSING	Non-fused
HORSEPOWER	5 hp/10 hp/20 hp/30 hp
MATERIAL	Copper-free aluminum
VOLTAGE RATING	240-600 Vac / 250 Vdc

00	
3D 00	SP3D Design Package - EID Explosionproof Compact Disconnect Switches
00000	IF 1532 - EID Disconnect Assembly
00000000	Eaton Specification Sheet - EIDA3030 S752 S784 EID Explosionproof Disconnect Switches
0000	EID Series Explosionproof, Compact Disconnect Switches Brochure
0000	EID Series Explosionproof, Compact Disconnect Switches catalog page
0000	EID Explosionproof, Compact Disconnect Switches UL certification EID Explosionproof, Compact Disconnect Switches Canadian certification

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

00:

