



□□□□□

Eaton EIDA3060 S784

Eaton Crouse-Hinds series EID disconnect switch, 60A, With switch, Non-fused, 10 HP/20 HP/40 HP, Copper-free aluminum, Auxiliary contact (single block), 240-600 Vac/250 Vdc

□□□□

PRODUCT NAME	Eaton Crouse-Hinds series EID disconnect switch
CATALOG NUMBER	EIDA3060 S784
UPC	662276155978
PRODUCT LENGTH/DEPTH	10.47 in
PRODUCT HEIGHT	12.47 in
PRODUCT WIDTH	9.65 in
PRODUCT WEIGHT	36 lb

□□□□	
SPECIAL FEATURES	Auxiliary contact (single block)
AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Zone 2 Class I, Division 1 Class I, Division 2 Class I, Zone 1 Class II, Division 1 Class III
NEMA RATING	3R
	9
	4
	3
	7
AMPERAGE RATING	60A
ENCLOSURE TYPE	With switch
FUSING	Non-fused
HORSEPOWER	10 hp/20 hp/40 hp
MATERIAL	Copper-free aluminum
VOLTAGE RATING	240-600 Vac / 250 Vdc

□□	
3D □□	SP3D Design Package - EID Explosionproof Compact Disconnect Switches
□□□□□	IF 1532 - EID Disconnect Assembly
□□□□□□□□	Eaton Specification Sheet - EIDA3060 S784 EID Explosionproof Disconnect Switches
□□□□	EID Series Explosionproof, Compact Disconnect Switches Brochure
□□□□	EID Series Explosionproof, Compact Disconnect Switches catalog page
□□□□	EID Explosionproof, Compact Disconnect Switches Canadian certification EID Explosionproof, Compact Disconnect Switches UL certification

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
□□:



□□□□
Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2025 □□ □□□□□□□□

Follow us on social media to get the latest product and support information.

