

Eaton EP-401548

Eaton S711 Soft starter, 560 A, 200 - 575 V AC, Us= 24 V DC, with control unit, Frame size 4, IP00

PRODUCT NAME	Eaton S711 soft starter
CATALOG NUMBER	EP-401548
PRODUCT LENGTH/DEPTH	545 mm
PRODUCT HEIGHT	204 mm
PRODUCT WIDTH	222 mm
PRODUCT WEIGHT	20.1 kg
CERTIFICATIONS	CE

TYPE	Soft starter for three-phase loads, with control unit and pump algorithm, DC Brake, Soft Brake, Jog, Bluetooth
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product

DECLARATIONS OF CONFORMITY

[eaton-soft-starter-declaration-of-conformity-uk251135en.pdf](#)

	standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
FITTED WITH:	Display Motor overload protection Internal bypass
POLLUTION DEGREE	3
CLASS	Adjustable
CLIMATIC PROOFING	5 to 95% Relative Humidity
CONNECTION TO SMARTWIRE-DT	No
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V
FRAME SIZE	FS4
ALTITUDE	Max 4000 m (Above 1000 m for detailed derating use S711 Select Software)
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MAX	70 °C
AMBIENT STORAGE	-40 °C

TEMPERATURE - MIN	
ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE	200 HP
ASSIGNED MOTOR POWER AT 220/230 V, 60 HZ, 3-PHASE	200 HP
ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE	450 HP
ASSIGNED MOTOR POWER IN-DELTA AT 220/230 V, 60 HZ	300 HP
ASSIGNED MOTOR POWER IN-DELTA AT 460/480 V, 60 HZ	600 HP
ASSIGNED MOTOR POWER IN-DELTA AT 575/600 V, 60 HZ	800 HP
EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	2520 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	0 W
MAINS VOLTAGE - MAX	632.5 V
MAINS VOLTAGE - MIN	170 V
OUTPUT VOLTAGE	250 V AC (relay outputs)
NUMBER OF OUTPUTS	3 Relay Outputs (1 fixed, 2 programmable)
VOLTAGE TYPE	DC
RATED OPERATIONAL VOLTAGE (UE) - MIN	200 V
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	575 V
RATED POWER THREE- PHASE MOTOR, INLINE, AT 230 V	160 kW
RATED POWER THREE- PHASE MOTOR, INLINE, AT 400 V	315 kW
RATED POWER THREE- PHASE MOTOR, INSIDE DELTA, AT 230 V	250 kW
RATED POWER THREE-	450 kW

PHASE MOTOR, INSIDE DELTA, AT 400 V	
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	140 W
VOLTAGE RATING - MAX	575 V
APPLICATION	<ul style="list-style-type: none"> • 3-phase motors: Yes • Soft starting of three-phase asynchronous motors
PROTECTION	Optional terminal cover for Finger and back-of- hand proof, Protection against direct contact
MOUNTING POSITION	As required
DROP-OUT VOLTAGE	0 - 16 V, DC operated
DEGREE OF PROTECTION	IP00 NEMA Other
FUNCTIONS	Single direction Torque control DC-Brake Soft-Brake Forward & reverse jog
OVERLOAD CYCLE	AC-53b: 3.5-20:580
PICK-UP VOLTAGE	19.2 - 28.8 V DC
RADIO INTERFERENCE CLASS	Class A (IEC 60947-4-2)
FAULT MEMORY	1000 Faults
INTERFACES	Modbus RTU (built-in) Bluetooth (built-in)
KICKSTART	600% (Kickstart current) Max. 2000 ms (Kickstart Duration)
RATED CONTROL VOLTAGE (UC)	24 V DC (-20 %/+20 %)
SUPPLY FREQUENCY	50/60 Hz, fLN, Main circuit
TERMINAL CAPACITY (STRANDED)	1 x (185 - 400) mm ² , Main cables 1x (1 - 2.5) mm ² , Control circuit cables
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	24 VDC
RATED CONTROL SUPPLY	24 VDC

VOLTAGE (US) AT DC - MIN	
RATED INSULATION VOLTAGE (UI)	600 V
RATED OPERATIONAL CURRENT (IE) AT AC-11	3 A
RATED OPERATIONAL CURRENT (IE) AT AC-53	560 A
RATED OPERATIONAL CURRENT (IE) AT AC-53, IN-DELTA	840 A
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	560 A
RATED OPERATIONAL POWER AT 220/230 V, 50 HZ	160 kW
RATED OPERATIONAL POWER AT 400 V, 50 HZ	315 kW
RATED OPERATIONAL POWER AT 500 V, 50 HZ	400 kW
RATED OPERATIONAL POWER IN-DELTA AT 220/230 V, 50 HZ	250 kW
RATED OPERATIONAL POWER IN-DELTA AT 400 V, 50 HZ	450 kW
RATED OPERATIONAL POWER IN-DELTA AT 500 V, 50 HZ	600 kW
RATED OPERATIONAL VOLTAGE (UE) - MAX	575 V
RAMP/RUN-UP TIME	180 s
SHOCK RESISTANCE	15 g, Mechanical
TIGHTENING TORQUE	0.5 Nm, Screw terminals, Control circuit cables 40 Nm, Main cables
START VOLTAGE	Max. 600% FLA, Min. 100% FLA, Soft start function
STARTUP CLASS	CLASS 20 (heavy starting duty 3 x I _e for 45 s) CLASS 10 (star-delta replacement) CLASS 30 (6 x I _e for 30 s)
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (185 - 400) mm ² , Main cables 1x (1 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY	1 x (185 - 400) mm ² , Main

(SOLID)	cables 1x (1 - 2.5) mm ² , Control circuit cables
TERMINAL CAPACITY (SOLID/STRANDED AWG)	1 x (350 - 750), Main cables 1x (28 - 12) , Control circuit cables

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

:



Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

