



□□□□□

Eaton FSQC2390 S4

Eaton Crouse-Hinds series Arktite FSQC interlocked receptacle with switch, Through feed, 0.39-1.20" cable dia, 3-wire, 4-pole, Brass contacts, Copper-free alum, Spring door, Special polarity, 3/4", For use with magnetic motor starters

□□□□

PRODUCT NAME	Eaton Crouse-Hinds series Arktite FSQC interlocked receptacle with switch
CATALOG NUMBER	FSQC2390 S4
UPC	782274011714
PRODUCT WEIGHT	10.72 lb

□□□□	
AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Zone 1 Class I, Division 2 Class II, Division 2 Class III Class I, Division 1 Class II, Division 1
NEMA RATING	12 9 3 7
SPECIAL FEATURES	Special polarity
TYPE	For use with magnetic motor starters
CONTACT MATERIAL	Brass
BACK BOX STYLE	Through feed
CONFIGURATION	Three-wire, four-pole
MATERIAL	Copper-free aluminum
RECEPTACLE STYLE	Spring door
TRADE SIZE	3/4"
CABLE DIAMETER	0.39-1.20 in

□□	
3D □□	SP3D Design Package - Arktite FSQC Explosionproof Interlocked Receptacles
□□□□□	IF 83 - FSQ Interlocked Receptacle and Switch - Class I, Group B Hazardous (Classified) Locations IF 926 - FSQ Interlocked Receptacle and Switch IF 748 - FSQ Receptacle Switch Replacement IF 1429A - FSQC - Replacing Collar Assembly
□□□□□□□	Eaton Specification Sheet - FSQC2390 S4
□□□□	Arktite FSQC Explosionproof Interlock Receptacles catalog page
□□□□	Arktite FSQC Explosionproof Interlock Receptacles Canadian certification Arktite FSQC Explosionproof Interlock Receptacles UL certification

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
□□:



□□□□
Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2025 □□ □□□□□□□□

Follow us on social media to get the latest product and support information.

