



Eaton FWP-4G14F

Eaton Bussmann series high speed cylindrical fuse, 700 V, 4 A, 200 kAIC, 14 x 51 mm, Non Indicating, Ferrule end x ferrule end

□□□□

PRODUCT NAME	Eaton Bussmann series high speed cylindrical fuse
CATALOG NUMBER	FWP-4G14F
UPC	051712691758
PRODUCT LENGTH/DEPTH	14 mm
PRODUCT HEIGHT	14 mm
PRODUCT WIDTH	51 mm
PRODUCT WEIGHT	19 g
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Recognized IEC Rated



Powering Business Worldwide

□□□□

AMPERAGE RATING 4 A

ACCESSORIES

- CH14 Modular fuse holder
- FW14-PCB

BREAKING CAPACITY 200 kA

FREQUENCY RATING - MAX 62 Hz

FREQUENCY RATING - MIN 45 Hz

FUSE INDICATOR Non Indicating

RELEASE CHARACTERISTIC Other

UTILIZATION CATEGORY gR (general purpose semiconductor protection)

VOLTAGE TYPE AC

FUSE SIZE 14 x 51 mm

RATED VOLTAGE AC 690 V

CLASS Class gR

CLEARING (I₂T) 17

WATT LOSSES 2.94 W

FUSE SHAPE Cylindrical

PRE ARC (I₂T) 5.6

INTERRUPT RATING 200 kAIC

CONNECTION Ferrule end x ferrule end

CONSTRUCTION SIZE 14 mm x 51 mm

MATERIAL Ceramic

PACKAGING TYPE Standard

VOLTAGE RATING 700 V

TYPE High speed fuse

APPLICATION Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

FUSE TYPE FWP-G14F

BREAKING CAPACITY AT NOMINAL VOLTAGE, AC 200 kA

□□

DECLARATIONS OF CONFORMITY

[eaton-high-speed-cylindrical-fuse-declaration-of-conformity-uk250950en.pdf](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:



 Eaton House
30 Pembroke Road
Dublin 4,
Eaton.com

© 2025

Follow us on social media to get the latest product and support information.

