



□□□□

Eaton PFMA-11-76-UNV1-M2

Eaton Crouse-Hinds series Champ Pro PFMA LED floodlight, 0.79 - 0.28A, Cool white, 3/4" entry, Heat and impact resistant glass lens, 11000 lumens, 158 lm/W, Die cast aluminum, Yoke mount, 7x6 optics, Gray epoxy powder coat, 100-277 Vac, 77W

□□□□

PRODUCT NAME	Eaton Crouse-Hinds series Champ Pro PFMA LED floodlight
CATALOG NUMBER	PFMA-11-76-UNV1-M2
UPC	662277153423
PRODUCT LENGTH/DEPTH	16.12 in
PRODUCT HEIGHT	14.94 in
PRODUCT WIDTH	9.94 in
PRODUCT WEIGHT	24.95 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Ordinary/Non-Hazardous Locations
STANDARDS TYPE	NEC/CEC
NEMA RATING	4X
INGRESS PROTECTION (IP) RATINGS	IP67 IP66

Product specifications

LAMP TYPE	LED
LUMENS	11000
LUMENS PER WATT	158
COLOR TEMPERATURE	Cool white
MOUNTING METHOD	Yoke
VOLTAGE RATING	100-277 Vac
FREQUENCY RATING	50/60 Hz
OPTICAL DISTRIBUTION	7x6
ENTRY SIZE	3/4"
LENS MATERIAL	Heat and impact resistant glass
WATTAGE	77W
DIMMING	Dimmable driver
POWER FACTOR	> 0.90
AMPERAGE RATING	0.79 - 0.28A
MATERIAL	Die cast aluminum

□□

3D □□

[SP3D Design Package -
Champ Pro PFMA LED
Industrial Floodlights](#)

□□□□□

[IF 1978 - PFMA M2 9L-15L
LED Luminaire](#)

□□□□□□□

[Crouse-Hinds series PFMA
LED Floodlights IES
photometric files](#)

□□□□

[Crouse-Hinds series
Champ PFMA LED
Floodlights - 9,000 to
15,000 lumens brochure](#)

[Crouse-Hinds series
Global LED lighting
portfolio](#)

□□□□

[Crouse-Hinds series
Champ PFMA LED
Floodlights - 9,000 to
15,000 lumens catalog
page](#)

