



□□□□□

Eaton TMCXM32 2

Eaton Crouse-Hinds series Terminator II TMCX cable gland,TSC compound,Cable Range:22.0-35.3 mm,Cable Sealing:2 (M),Metal-cladcorrugated armoured,TECK armoured,armoured barrier and tray cable,Armoured gland, Aluminum, M32

□□□□

PRODUCT NAME	Eaton Crouse-Hinds series Terminator II TMCX cable gland
CATALOG NUMBER	TMCXM32 2
UPC	662276299054
PRODUCT LENGTH/DEPTH	4.38 in
PRODUCT HEIGHT	2.56 in
PRODUCT WIDTH	2.56 in
PRODUCT WEIGHT	1.15 lb



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class II, Division 1 Class III
NEMA RATING	4X 6P

Product specifications

PROTECTION TYPE	Explosion-proof
CABLE TYPE	Tray cable TECK armoured Metal-clad with interlocked or continuously welded corrugated armoured Armoured barrier
GLAND TYPE	Armoured
THREAD SIZE	M32
THREAD TYPE	Metric
CABLE SEALING RANGE	2 (M)
CABLE RANGE (MIN/MAX)	22.0-35.3 mm
MATERIAL	Aluminum
BARRIER TYPE	TSC Compound

□□

3D CAD DRAWING PACKAGE	Eaton Crouse-Hinds TMCXM32 2 3D drawing
□□□□□	IF 1647B - TMCX Terminator II Cable Gland IF 1647 - TMCX Terminator II Cable Gland
□□□□□□□	Eaton Specification Sheet - TMCXM32 2
□□□□	Crouse-Hinds series Chico LiquidSeal flyer Crouse-Hinds series TMCX II brochure
□□□□	Crouse-Hinds series TMCX II catalog page
□□□□	TMCX II Explosionproof Armoured Barrier and Non-armoured Barrier Gland UL certification TMCX II Explosionproof Armoured Barrier and Non-armoured Barrier Gland Canadian certification

