Eaton TMF355

Eaton Bussmann series low voltage british standard fuse, 355A, AC 660 V, DC 460 V, V88/B4, $60 \times 137 \text{ mm}$, gL/gG

| Eaton Bussmann series low voltage british standard fuse |
|---|
| TMF355 |
| 137 mm |
| 60 mm |
| 60 mm |
| 664 g |
| CE Marked RoHS Compliant |
| BS88 IEC 60269 EAC |
| |



| AMPERAGE RATING | 355 A |
|--|---|
| FITTED WITH: | Centre bolted tags |
| FUSE SIZE | BS88/B4 |
| CURRENT TYPE | AC/DC |
| MOUNTING DIMENSION | M8 |
| CENTER-TO-CENTER DISTANCE OF CONNECTIONS | 111 mm |
| BREAKING CAPACITY | 80 kA |
| RATED SWITCHING CAPACITY | 80 kA |
| RATED VOLTAGE AC | 660 V |
| RATED VOLTAGE DC | 460 V |
| CLASS | Class gG/gL |
| FUSE TYPE | TMF |
| UTILIZATION CATEGORY | gL/gG (cable protection/equipment protection) |
| COLOR | None |
| INTERRUPT RATING | 80 kAIC |
| FUSE INDICATOR | None |
| INSULATED METAL GRIPPING LUGS (IMGL) | No |
| CONNECTION | 111 mm fixing centre |
| CONSTRUCTION | BS88/B4 |
| CONSTRUCTION SIZE | Other |
| FUSE SHAPE | Center bolted tags |
| VOLTAGE TYPE | AC/DC |
| VOLTAGE RATING | 660 V |
| ТҮРЕ | Fuse |
| APPLICATION | general industrial applications |
| FUSE SYSTEM (ACCORDING TO IEC 60269) | Fuse system E |

DECLARATIONS OF CONFORMITY

eaton-low-voltage-britishstandard-fuse-declarationof-conformityuk250884en.pdf

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| : | |



Eaton House 30 Pembroke Road Dublin 4, Eaton.com

Follow us on social media to get the latest product and support information.









