Eaton U280-016-RM

16-Port USB Charging Station with Syncing Function - 5V 40A / 200W USB Charger Output

PRODUCT NAME	Eaton Tripp Lite series rackmount charging station
CATALOG NUMBER	U280-016-RM
UPC	037332182715
PRODUCT LENGTH/DEPTH	9.45 in
PRODUCT HEIGHT	1.71 in
PRODUCT WIDTH	17.32 in
PRODUCT WEIGHT	7.17 lb
COMPLIANCES	FCC Class B RoHS REACH
CERTIFICATIONS	UL 60950-1 IEC 60950-1 NOM CSA Std. C22.2

Powering Business Worldwide

□□□□	
FREQUENCY RATING	50/60 Hz
CHARGING PORTS DETAILS	USB-A: 5V/2.4A
NUMBER OF CHARGING PORTS	16
TOTAL CHARGING AMPS	40A
TOTAL CHARGING WATTS	200
PRODUCT TYPE	Charging Station
FEATURES	Flex Center
DEVICE COMPATIBILITY	Tablet Amazon Kindle Phone
FREQUENCY COMPATABILITY	50/60 Hz
COLOR	Black
INPUT PLUG TYPE	NEMA 5-15P
MATERIAL	Steel
CHARGING PORTS / AMPS	2.4A
INPUT CONNECTION TYPE	IEC320-C14
INPUT CURRENT	2.5A
INPUT FREQUENCY	50/60Hz
CHARGING METHOD	USB
INPUT NOMINAL VOLTAGE	120 VAC 240 VAC
PRODUCT FEATURES	IEC320-C14
RELATIVE HUMIDITY	5% to 95% RH, Non-Condensing
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
STORAGE TEMPERATURE RANGE	5° to 122°F (-15° to 50°C)
PACKAGE CONTENTS	USB 2.0 A/B Device Cable Mounting Hardware C13 to 5-15P Power Cord Rubber Feet U280-016-RM Owner's Manual
PRODUCT HIGHLIGHTS	Sync and charge up to 16 tablets, phones, or other mobile device Mounting hardware included for use in a rack installation Provides up to 5V, 2.4A (12 Watts) of power per port, for charging battery-

□□

	intensive devices such as an iPad Sync your devices using their file management software, such as Apple iTunes or Apple Configurator Supports USB 2.0 data transfer rates up to 480Mbps Charge your devices without the need to connect to a computer
CHARGING FORM FACTOR	Rack mount
CHARGING PORT TYPE	USB A (FEMALE)
PACKAGING TYPE	Box
BTUS	160.6 BTU/Hr (Full Load)
LED INDICATORS	Green (16x USB Charging, 1x Sync)
NUMBER OF PORTS	16
OVERLOAD PROTECTION	No
POWER CONSUMPTION	47 W
TAA COMPLIANCE	No
SIDEA CONNECTOR1	USB A (FEMALE)
SIDEB CONNECTOR1	IEC-320-C14 USB B (FEMALE)
SIDEA CONNECTOR2	USB B (FEMALE)
SIDEA CONNECTOR3	MICRO-USB B (FEMALE)
VOLTAGE COMPATIBILITY (VAC)	100 VAC 110 VAC 120 VAC 125 VAC 127 VAC 200 VAC 208 VAC 220 VAC 230 VAC 240
CHARGING AMPS PER PORT	2.4 A 2.4A

□□□□:	
□□□□:	
□□□:	
□□:	

□□□□ Eaton House
30 Pembroke Road
Dublin 4, □□□
Eaton.com

© 2026 □□ □□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□