

# Eaton

## UTL1102G1W3S14AWG

Evaluation kit, with female in line receptacle and contacts, 2G1W3 layout;  
UTL1102G1W3S14AWG

PRODUCT NAME	Eaton Souriau UTL series uL/IEC power and control supply
CATALOG NUMBER	UTL1102G1W3S14AWG
PRODUCT LENGTH/DEPTH	28.6 mm
PRODUCT HEIGHT	28.6 mm
PRODUCT WIDTH	28.6 mm
PRODUCT WEIGHT	14.3 g
COMPLIANCES	UL 1977 (please contact us for more details) IEC 61984 (please contact us for more details)

<b>CURRENT RATING</b>	16 A IEC 16 A UL
<b>FITTED WITH:</b>	Layout with ground cavity First mate last break capability
<b>ENVIRONMENTAL CONDITIONS</b>	RoHS REACH Flammability rating UL94 V0
<b>ENVIRONMENTAL RESISTANCE</b>	Resistant against gasoline Resistant against basic bath Resistant against acid bath  Resistant against oil UV resistant, no degradation after 5 years of exposure in natural environment Resistant against mineral oil
<b>TEST CURRENT</b>	16 A UL16 A IEC
<b>TEST VOLTAGE</b>	600 V UL 500 V IEC
<b>CONNECTOR ACCESSORY OPTION</b>	Only to be overmolded
<b>CONNECTOR TYPE</b>	Receptacle
<b>CONTACT DELIVERY</b>	Unloaded
<b>CONTACT GENDER</b>	Socket (Female)
<b>CONTACT TYPE</b>	Crimp
<b>COUPLING TYPE</b>	Push-Pull
<b>DEGREE OF PROTECTION</b>	IP68
<b>INSERT MATERIAL</b>	Polyamide
<b>LAYOUT</b>	2G1W3
<b>SHELL MATERIAL</b>	Plastic
<b>SHELL SIZE</b>	10
<b>MATING CYCLES</b>	1000
<b>OPERATING TEMPERATURE - MAX</b>	105 °C
<b>OPERATING TEMPERATURE - MIN</b>	-40 °C
<b>RECEPTACLE TYPE</b>	In-Line Receptacle
<b>NUMBER OF CONTACTS</b>	6
<b>NUMBER OF CAVITY #16</b>	3
<b>NUMBER OF CAVITY #20</b>	3



SALT SPRAY	1000 hour
------------	-----------

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
:



Eaton House  
30 Pembroke Road  
Dublin 4,  
Eaton.com  
© 2025

Follow us on social media to get the latest product and support information.

