## Eaton UTS1JC147P

Plastic in line receptacle, with cable gland backshell, for 7 male contacts, IP68/69K; UTS1JC147P

PRODUCT NAME	Eaton Souriau UTS series plastic waterproof IP68/69k connector
CATALOG NUMBER	UTS1JC147P
PRODUCT LENGTH/DEPTH	78.5 mm
PRODUCT HEIGHT	35.1 mm
PRODUCT WIDTH	35.1 mm
PRODUCT WEIGHT	43.9 g
COMPLIANCES	CSA-C22.2 No.182.3 (please contact us for more details) IEC 61984 (please contact us for more details) UL 1977 (please contact us for more details)



CURRENT RATING	16 A IEC
FITTED WITH:	Last mate first break capability(optional) First mate last break capability Layout with ground cavity
ENVIRONMENTAL CONDITIONS	Fire & Smoke REACH ROHS Flammability rating UL94 V0 Fire and smoke rating I2F3 according to NFF 16101 and NFF 16102
ENVIRONMENTAL RESISTANCE	Resistant against mineral oil Resistant against basic bath Vibrations level Per IEC 60512-4 - from 10 to 2000 Hz Resistant against acid bath Resistant against gasoline Resistant against oil UV resistant, no degradation after 5 years of exposure in natural environment
TEST CURRENT	10 A UL 16 A IEC 7 A CSA
TEST VOLTAGE	500 V CSA 300 V IEC 500 V UL
BACKSHELL ANGLE	Straight
BACKSHELL TYPE	Sealing Gland
CONNECTOR ACCESSORY OPTION	Delivered with connector
CONNECTOR ORIENTATION	N
CONNECTOR TYPE	Receptacle
CONTACT DELIVERY	Not delivered
CONTACT GENDER	Pin (Male)
CONTACT TYPE	Crimp
COUPLING TYPE	1/3 Bayonet
DEGREE OF PROTECTION	IP68

INSERT MATERIAL	Polyamide
LAYOUT	7
SHELL MATERIAL	Plastic
SHELL SIZE	14
CABLE DIAMETER - MAX	14 mm
CABLE DIAMETER - MIN	5 mm
MATING CYCLES	250
OPERATING TEMPERATURE - MAX	105 °C
OPERATING TEMPERATURE - MIN	-40 °C
RECEPTACLE TYPE	In-Line Receptacle
NUMBER OF CONTACTS	7
NUMBER OF CAVITY #16	7
SALT SPRAY	500 hour

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
:	



Eaton House 30 Pembroke Road Dublin 4, Eaton.com

Follow us on social media to get the latest product and support information.









