

Eaton UTS712D14P32

Plastic jam nut receptacle & hold down clips,without backshell, with 14 male PCB contacts, IP68/69K in unmated conditions; UTS712D14P32

PRODUCT NAME	Eaton Souriau UTS series plastic waterproof IP68/69k connector
CATALOG NUMBER	UTS712D14P32
PRODUCT LENGTH/DEPTH	25.3 mm
PRODUCT HEIGHT	31.8 mm
PRODUCT WIDTH	31.8 mm
PRODUCT WEIGHT	16.1 g
COMPLIANCES	ROHS exemption 6.c UL 1977 (please contact us for more details) IEC 61984 (please contact us for more details) CSA-C22.2 No.182.3 (please contact us for more details)

CURRENT RATING	5 A IEC 4.5 A UL
ENVIRONMENTAL CONDITIONS	Flammability rating UL94 HB REACH RoHS
ENVIRONMENTAL RESISTANCE	Resistant against acid bath
	Vibrations level Per IEC 60512-4 - from 10 to 2000 Hz
	Resistant against oil
	Resistant against basic bath
	UV resistant, no degradation after 5 years of exposure in natural environment
TEST CURRENT	Resistant against gasoline
	Resistant against mineral oil
TEST VOLTAGE	4.5 A CSA 5 A IEC 4.5 A UL
CONNECTOR ACCESSORY OPTION	250 V CSA 250 V UL 32 V IEC
CONNECTOR ORIENTATION	No backshell possibility
CONNECTOR TYPE	N
CONTACT DELIVERY	Receptacle
CONTACT GENDER	Loaded
CONTACT PLATING	Pin (Male)
CONTACT TYPE	Gold
COUPLING TYPE	PCB
DEGREE OF PROTECTION	1/3 Bayonet
INSERT MATERIAL	IP68
LAYOUT	Neoprene
SHELL MATERIAL	14
SHELL SIZE	Plastic
MATING CYCLES	12
OPERATING TEMPERATURE - MAX	250
OPERATING TEMPERATURE - MIN	105 °C
	-40 °C

RECEPTACLE TYPE	Jam Nut Receptacle
NUMBER OF CONTACTS	14
NUMBER OF CAVITY #20	14
NUT MATERIAL	Aluminium
SALT SPRAY	500 hour

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
: